

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 2

Alias	Description

Survey by John E. Hollingsworth, L.S. #691 - For: Oregon State Parks and Recreation - June/Aug. 1988 - C.S. File 63/62 and M 107-16

Set 5/8" x 30" Iron rod with alum. cap 26" in ground. Cap mkd. "T33S R6W C $\frac{1}{4}$ S2 1988 Oregon State Parks Division".
New BTs -13" Fir bears N.22°E., 16.29 ft. to 2 finish nails side and center, mkd. "XBT"
14" Fir bears N.43°W., 19.55 ft. to 2 finish nails side and center, mkd. "C $\frac{1}{4}$ S2 BT"
Set orange carsonite with decal mkd. "Property Boundary State Park Land Behind This Sign", 2 ft. NE.

Fd. OK by Nygren, June 1998 - M130-10

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2925; Surveyed July/Oct. 2018 - (DCSO records Vol. 59 Page(s) 23784-5)

The center $\frac{1}{4}$ sec cor of sec. 2, established by Hollingsworth, in 1988, and is accepted as the cor.; monumented with an iron rod, 5/8" dia., firmly set, projecting 10" above the ground, with aluminum cap mkd. T33S R6W C $\frac{1}{4}$ S2 1988 OREGON STATE PARKS DIVISION, from which bearing trees mkd. by Hollingsworth
A fir, 21" dia., bears N.15 $\frac{1}{2}$ °E., 15.5 ft., with a healed blaze.
A fir, 21" dia., bears N.48°W., 19.8 ft., with a healed blaze.
At the corner point
Set a stainless steel post, 28" long, 2 $\frac{1}{2}$ " dia., 25" in the ground, directly over the iron rod, with brass cap mkd.
T33S R6W
C $\frac{1}{4}$ S 2
2018