

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 2 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8636)

Set ¼ sec. post on N. slope, from which
A Fir 20" dia., bears S.21°E., 40 lks.
A Fir 16" dia., bears S.62°W., 122 lks.

Not Fd by J.Powell, DCSO 10/1967 (added 3/28/2017) C.S. 54/53-35

Survey by R.A. Brandt - For: Robert Dollar Co. - Jan/May 1973 - C.S. File 55/294 and M 49-21

Set 1" x 36" I.Rod, 4" high, from which bears
14.1" D.Fir S.25°44'W., 18.68 ft. mkd. ¼ S2 PS841 BT.
13.4" D.Fir S.44°39'E., 28.5 ft. mkd. ¼ S2 PS841 BT.
Also an old D.Fir stump showing evidence of early corner search bears S.28°23'E., 44.0 ft. from the corner as set, however, compared with the original BT (bearing from the corner a 20" D.Fir S.21°E., 26.4 ft.) the corner would be placed 11.45 ft. East and 14.06 ft. South of the corner as established.

Survey by John E. Hollingsworth, L.S. #691 - For: Oregon State Parks & Recreation - June/Aug. 1988 - C.S. File 63/62 and M 107-16

(No original evidence found)
Found - 1" Iron rod set by Brandt in 1973 and references as per Brandt.
I do not agree with the method of proportioning used to set this corner and I therefore set a new monument for the corner.
Set 1" x 30" iron post with a 2 3/8" brass cap at single proportioned distance between the North standard ¼ corner Sec. 4 and the Standard cor. secs. 35 and 36 on a latitudinal curve. Cap mkd: "Oregon State parks T32S R6W ¼ S2 T33S R6W 1988 LS 691".
New measurements to existing bearing trees:
A 16" Fir bears S.47°E., 28.9 ft. with healed blaze.
A 15" Fir bears S.23°W., 16.6 ft. with healed blaze.
Set orange carsonite post with decal mkd. "Property Boundary State Park Land Behind This Sign", 2 ft. southeast.

FD. Ok by Mark Heimburger 11/2006 - M151-65

continued next page

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 2 only

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2125, surveyed July 2006/Feb. 2007 - (DCSO records Vol. 55 Page(s) 21433-4)

 The standard ¼ sec. cor. of sec. 2, on the N. bdy. of T33S R6W bears, N.89°39'53"W., 2450.78 ft. reestablished by proportionate measurement, by Hollingsworth, in 1988, utilized by various Oregon Professional Surveyors, there is no remaining evidence of the original cor.; this position was verified and is accepted as the cor.; monumented with an iron post 1¼" dia., firmly set, projecting 4" above the ground, with a brass cap 2½" dia., mkd.

OREGON STATE PARKS

T32S R6W

¼ S 2

T33S R6W

1988

LS 691

From this corner, a point established as the ¼ sec. cor. of sec. 2 by Ronald A. Brandt, in 1973, bears N.38°03'E., 2.60 ft., monumented with an iron rod, 1" dia., firmly set, projecting 4" above the ground, and was not used for control in this survey, from which bearing trees mkd. by Brandt

A D.Fir, 18" dia., bears S.45°E., 29.1 ft., with a healed blaze.

A sawed Douglas fir stump, 19" dia., bears S.25¾°W., 18.7 ft., with a healed blaze.

DCSO-GIS Corner visitation - 4/13/2005 - Typed: 2/10/2011 - C.S. File 67/33-1

 Monument - 2½" BC on 1" IP Comment - OK

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2925; Surveyed July/Oct. 2018 - (DCSO records Vol. 59 Page(s) 23785-6)

 The ¼ sec. cor. of sec. 2 only, on the N. bdy. of the Tp., reported by Dieckmann in 2006-07, monumented with an iron post, 1¼" dia., firmly set, projecting 3" above the ground, with brass cap (properly) mkd. from which a new bearing tree

A fir, 8" dia., bears S.4¾°W., 40.2 ft., mkd. ¼ S2 BT.

From this cor., a point reported by Dieckmann, bears N.38°03'00" E., 2.60 ft., monumented with an iron rod, 1" dia., firmly set, projecting 2" above the ground, from which a bearing tree reported by Dieckmann

A fir, 19" dia., bears S.45°E., 29.1 ft., with a healed blaze.