

PRIMARY CORNER DESCRIPTION Sec Cor. for Secs. 1, 2, 11 & 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

**Not in Douglas County**

Original - GLO survey by Wells Lake and Geo. W. Hyde, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 21 Page(s) 9003)

-----  
Set post cor. to secs. 1, 2, 11 and 12, from which

- A B.Oak 3" dia., bears N.18°W., 20 lks.
- A B.Oak 4" dia., bears N.48°E., 14 lks.
- A B.Oak 3" dia., bears S.50°E., 22 lks.
- A Laurel 3" dia., bears S.58°W., 8 lks.

-----  
Survey by John Hollingsworth, LS #691 - For: Oregon State Parks and Recreation - June/Aug. 1988 - C.S. File 63/62 and M 107-16

-----  
Found - 1½" Iron pipe 6" above ground from which no evidence of original BTs.

A 15" B.Oak bears N.26°E., 18.0 ft. with sawed into healed blaze.

No evidence of 8" Madrone and the BTs mkd. by Reece.

A down 14" Fir bears S.30°E., 4.9 ft., no scribing visible.

A 15" B.Oak bears S.35°W., 51.7 ft. (24.7) with "CS S11 BT" visible in partially healed blaze.

A 14" Fir bears N.20°W., 24.7 ft. with healed blaze.

New Accessories:

8" Madrone bears S.58°E., 28.0 ft. mkd. "T33S R6W S12 BT"

Set orange corsonite post with decal mkd. "Property Boundary State Park Land Behind This Sign", 2 ft. NW.

-----  
BLM dependent resurvey by Francis J. Simon, Cadastral Surveyor under Group #1736, surveyed June/Sept. 1994 - (DCSO records Vol. 52 Page(s) 19722-3)

-----  
From the cor. of secs. 1, 2, 11, & 12, restored by person(s) unknown & utilized by Lawrence, in 1955, utilized by Thompson, in 1962, perpetuated by Reece, in 1982, & further perpetuated by Hollingsworth, in 1988, & accepted as the corner; monumented w/an iron pipe, 1½ ins. diam., firmly set, projecting 1" above the ground; from which a BT reported by Thompson:

A B.Oak, 15" diam. bears N.22°E., 27½ lks. w/healed blaze. and the remains of bearing trees mkd. by Reece

A dead & down fir, 14" diam., bears S.30°E., 7½ lks. no marks visible.

continued next page

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A B.Oak, 17" diam., bears S.35°W., 78½ lks., with healed double blaze.  
A fir, 16" diam., bears N.20°W., 37½ lks., with healed blaze.  
and a bearing tree mkd. by Hollingsworth  
A madrone, 9" diam., bears S.58°E., 42½ lks. dist., with scribe marks T33S R6W S12 BT visible on a partially healed blaze.  
At the corner point  
Set a stainless steel post, 28" long, 2½ ins. diam., 24" in the ground, directly over the iron pipe, with brass cap mkd.  
T33S R6W  
S 2 S 1  
S 11 S 12  
1994  
Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

**See Josephine County Surveyor's Office for the most current information.**