

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wells Lake and Geo. W. Hyde, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 21 Page(s) 9004)

-----  
Set quarter sec. post, from which  
A Laurel 3" dia., bears S.61°E., 8 lks.  
A Laurel 3" dia., bears S.72°W., 21 lks.

Survey by Robert M. Thompson - For: Glendale Stud - March 1962 C.S. File 51/171

-----  
Original ¼ corner not found.  
Corner set at proportionate distance.  
Set 3/4" I.Pipe and scribed:  
30" D.Fir S.68°30'W., 30.6 ft.  
10" Madrone N.61°00'E., 13.0 ft.

Survey by John E. Hollingsworth - For: Oregon State Parks and Recreation - June/Aug. 1988 - C.S. File 63/62 and M 107-16

-----  
Found - Thompson's 3/4" Iron pipe and BTs but I set a new ¼ corner as Thompson's I.P. is about 8.5 ft. out of position.  
Set 1" x 30" I.P., 26" in ground with 2 3/8" brass cap at single proportioned position. Cap mkd. "Oregon State Parks T33S R6W ¼ S2|S1 1988 LS 691"  
New Measurements to existing BTs:  
10" Madrone bears N.58°E., 21.6 ft. with illegible scribe marks in partially healed blaze.  
32" Fir bears S.81°W., 24.0 ft. to center with healed blaze.  
A 3/4" Iron pipe bears N.41°41'E., 8.56 ft.  
Set orange carsonite post with decal mkd. "Property Boundary State Park Land Behind This Sing", 2 ft. West.

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2925; Surveyed July/Oct. 2018 - (DCSO records Vol. 59 Page(s) 23786)

-----  
The ¼ sec. cor. of secs 1 & 2, reestablished by proportionate measurement by Hollingsworth, in 1988. There is no remaining evidence of the original cor., therefore this position is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron post, 1" dia., firmly set, projecting 5" above the ground, with brass cap (properly) mkd from which BTs mkd. by Thompson, PE No. 3683, in 1962, and reported by Hollingsworth  
continued next page

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A madrone, 13" dia., bears N.55°E., 21.2 ft., with a healed blaze.  
A fir, 38" dia., bears S.76¼°W., 23.9 ft., with a healed blaze.  
From this cor., a point established by Thompson, in 1962, bears N.41°50'50"E., 8.54 ft., monumented with an iron pipe, 3/4" dia., firmly set, projecting 7" above the ground, not accepted by Hollingsworth in 1988, and not utilized during the course of this survey.