

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; & Sec. 6, T33-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Butler Ives and George W. Hyde, under Contract #39, dated January 4, 1854 - (DCSO records Vol. 21 Page(s) 8949)

-----  
Set ¼ sec. post, from which  
A B.Oak 14" dia., bears S.32°W., 48 lks. dist.  
A B.Oak 12" dia., bears S.60°E., 13 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy, J.M. Powell and crew - March 19, 1968 - C.S. File 49/112

-----  
Found - Orig. 14" B.Oak now stump, S.34°W. (Rec. S.32°W.) 31.7 ft., opened for scribe "BT".  
Orig. 12" now 23" B.Oak, S.60°E., 8.6 ft., shows scar.

Set Brass cap at cor. mkd: County Surveyors Office  
Doug. Co.  
R T 33 S R  
6 ¼ S 1 S 6 5  
W Jos. Co. W

New BT - 11" D.Fir S.31°W., 24.3 ft. mkd. ¼ S1 CS BT.  
Reblazed and rescribed:  
23" B.Oak S.60°E., 8.6 ft. mkd. ¼ S6 CS BT.  
Corner lies approx. 35.0 ft. S. of ridge top, ridge running E-W.

Fd. & used on BLM dependent resurvey by Terrence O. Nickerson, Cadastral Surveyor under Group #1474 survey Feb. 1989/June 1992 - (DCSO records Vol. 53 Pg(s) 20358-9)