

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION West Cor. Secs. 6 & 7, only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

NOT IN DOUGLAS COUNTY

GL0 survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCS0 records Vol. 21 Page(s) 9046)

Set a sandstone, 14x12x10", 10" in the ground, for cor. of secs. 1, 6, 7, & 12, marked with 1 notch on N and 5 notches on S. edges, from which:

A Fir, 40" dia., bears N.38°E., 48 lks., mkd. T33S R7W S6 BT.

A Fir, 30" dia., bears S.54°E., 37 lks., mkd. T33S R7W S7 BT.

A Chinquapin, 6" dia., bears S.57°W., 84 lks., mkd. T33S R8W S2(?) BT.

A Fir, 24" dia., bears N.76°W., 72 lks., mkd. T33S R8W S1 BT.

This corner stands 20' below top of ridge.

GL0 Resurvey by Norman D. Price, U.S. Surveyor and Ira Shaffner, U.S. Transitman Under Special Instructions dated Sept. 22, 1916 (DCS0 records, Volume 21 Page(s) 9063)

The corner established for sec. 1, 6, 7, & 12, which is a sandstone, 12x10x5", above ground, firmly set, mkd. and witnessed as described by the surveyor general.

Hereafter this cor. will refer to secs. 6 & 7 only.

Obliterated markings on bearing trees referring to secs. W. of line.

BLM remonumentation survey by Joseph S. Gawron, Cadastral Surveyor, under instructions dated May 1957, Group #350, surveyed May/June 1966 (DCS0 records Vol. 34 Page(s) 14134-5)

The cor. of secs. 6 & 7 only, on the W. bdy of the Tp., determined at record bearing and distance from the original bearing trees:

A fir, 46" dia., bears N.38°E., 48 lks., with illegible scribe marks visible on bark blaze.

A fir, 28" dia., bears S.54°E., 37 lks., mkd. T33S R7W S7 BT on bark blaze.

A down chinquapin, 8" dia., bears S.57°W., 84 lks., marks destroyed by Price and Shaffner.

A fir, 16" dia., bears N.76°W., 72 lks., marks destroyed by Price and Shaffner.

At the corner point
(Cont. Next Page)

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION West Cor. Secs. 6 & 7, only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set an I.P. 28" long, 2½" dia. 24" in the ground, w/brass cap
T33S | T33S
R8W | S 6
 | S 7
 | R7W
 1966
From which new bearing trees
A chinquapin, 6" dia., bears N.25°E., 90 lks., mkd. T33S
R7W S6 BT.
A fir, 26" dia., bears S.38°E., 70 lks., mkd. T33S R7W S7
BT.

Fd. per Josephine Co. Records by D Meade 5/2024 - M184-10

See Josephine County Surveyor's Office
for the most current information.