

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 100638

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 1 only, T33-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Norman D. Price, U.S. Surveyor and Ira Shaffner, U.S. Transitman, under Instructions dated Sept. 22, 1916 (DCSO records Vol. 21 Page(s) 9064)

Set a granite stone 15 x 10 x 8 ins., 10" in the ground for 1/4 cor. of sec. 1, mkd. 1/4 on W. face, from which
A Madrona 20" dia., bears S.20°W., 40 lks. dist., mkd. 1/4 S1 BT.
A Fir 10" dia., bears N.18°W., 45 lks. dist., mkd. S1 BT.

Douglas Co. Surveyors Office - Frank Jones & crew - May/June 1968 - C.S. File 54/36-186

Found - No trace of corner stone or SW BT due to logging.
10" D.Fir now 26" snag, N.18°W., 29.7 ft. opened and found scribing.

Set Brass cap at cor. mkd: County Surveyors Office
T 33 S
R8W 1/4 S 1 | Doug. Co.
1968

New BTs -22" D.Fir S.82°W., 50.9 ft. mkd. 1/4 S1 CS BT.
40" Y.Pine S.35°W., 52.0 ft. mkd. 1/4 S1 CS BT.