

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Section 6 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 21 Page(s) 9046)

Set a granite stone 15 x 12 x 10 ins., 10" in the ground, for 1/4 sec. cor., mkd. 1/4 on W. face, from which
A Fir 24" dia., bears N.33 1/4°E., 23 lks. dist., mkd. 1/4 S6 BT.
A Fir 44" dia., bears S.2 1/2°W., 49 lks. dist. mkd. 1/4 S1 BT

GL0 resurvey by Norman D. Price, U.S. Surveyor and Ira Shaffner, U.S. Transitman, under Instructions dated Sept. 22, 1916 (DCSO records Vol. 21 Page(s) 9064)

The 1/4 cor. established for secs. 1 and 6, which is a granite stone, 12 x 10 x 5 ins., above ground, firmly set, mkd., and witnessed as described by the surveyor general.
Hereafter this cor. will refer to sec. 6 only.
Reset Stone with 1/4 facing E.
Obliterate markings on bearing tree referring to sec. 1 and take new bearing tree as follows:
A Fir 20" dia., bears N.25°E., 33 lks. dist., mkd. 1/4 S6 BT

Douglas Co. Surveyors Office - V.R. Tracey & crew - May 1968 - C.S. File 54/36-185

Found - Corner stone, 12x10x5 mkd. "1/4".
20" D.Fir now 28" snag, N.25°E., 21.8 ft., opened and found scribing, 1/4 S6
Set Brass cap at cor. mkd: County Surveyors Office
T 33 S R 7 W
1/4 | S 6 Doug. Co.
Jos. Co |
1968
New BTs -40" D.Fir N.85°E., 95.3 ft. mkd. 1/4 S6 CS BT.
26" D.Fir snag, N.32 1/2°E., 16.3 ft. mkd. 1/4 S6 CS BT.
There are no other living trees in range for scribing and this corner lies 264 ft. South of top of ridge.

Fd. per Record by D Meade 5/2024 - M184-10