TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION NW Cor. Section 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 21 Page(s) 9047)

I Set a Pine post, 3 ft. long, 4" sq., 24" in the ground, for closing cor. of secs. 1 and 6, Tp. 33 S., Rs. 7 and 8 W., mkd. CC T33S on S.; R7W S6 on E.; and R8W S1 on W. faces, with 6 grooves on SE., and W. faces, from which

A Fir 6" dia., bears S.19°W., 131 lks. dist. mkd. T33S R7W S6 BT.

A Fir 24" dia., bears S.58°W., 56 lks. dist., mkd. T33S R8W S1 BT.

BLM resurvey by Norman D. Price, U.S. Surveyor and Ira F. Shaffner, Transitman, under Instructions dated Sept. 22, 1916. (DCSO records Vol. 21 Page(s) 9064-65)

The closing cor. of Tps. 33 S., Rs. 7 and 8 W., which is a Pine post, 4 x 4 ins., 12" above ground, firmly set, mkd. and witnessed as described by the surveyor general. Alongside of Post,
Set a limestone 20x14x10 ins., 15" in the ground, mkd. with 6 grooves on E., S. and W. faces and CC on S. face.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley, crew - March 1968 - C.S. File 54/36-120

Found - Stone 20x14x10 ins., with 6 notches.
24" D.Fir now 26" snag, S.58°W., 37.0 ft. found bark scribing, T33, R, BT

Set Brass cap at cor. mkd: County Surveyors Office

```
R   T32S   R
8          7
W  S 1|S 6 W
     C C
     1968
```

New BTs -14" D.Fir S.14°E., 65.7 ft. mkd. T33S R7W S6 CC CS BT.
6" Pine S.41°W., 45.7 ft. mkd. S1 CC CS BT.

This corner lies 150 ft. East of logging road.

Fd. per Record by D Meade 5/2024 - M184-10