

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

NOT IN DOUGLAS COUNTY

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 21 Page(s) 9054)

Set a fir post, 3 ft. long, 3" square, 24" in the ground for ¼ sec. cor., mkd. ¼ S 8 on N and 17 on S. face, from which:
A Fir, 6" dia, bears N.11°W., 35 lks., mkd. ¼ S8 BT.
A Sugar Pine, 50" dia. bears S.23°W. 26 lks. mkd ¼ S17 BT.
This corner stands 450' below top of ridge, begin gradual descent of NW slope.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #845, surveyed April/Nov. 1975 (DCSO records Vol. 41 Page(s) 16284)

The ¼ sec. cor. of secs. 8 & 17, perpetuated and recorded by Max W. Hull, L.S. #901, in 1973, monumented with an iron rod, 5/8" dia., firmly set, projecting 4" above ground, with plastic cap mkd. RS 901, from which the remains of the original BTs:

A fir, 17" dia., bears N.11°W., 35 lks., with scribe marks
BT visible on opened blaze.

A sugar pine, 50" dia., bears S.23°W., 30 lks., no marks visible. (Record, 26 lks.)

At the corner point

Set a iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron rod, with brass cap mkd:

T33S R7W

¼ $\frac{S 8}{S 17}$
1975

from which a new bearing tree

A cedar, 25" dia., bears S.42°W., 82 lks., mkd. ¼ S17 BT.

**See Josephine County Surveyor's Office for
the most current information.**