

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 (DCSO records Vol. 21 Page(s) 9058)

Set a granite stone 15 x 12 x 7 ins., 10" in the ground, for 1/4 sec. corner, marked 1/4 on N. face, from which

A Fir 18" dia., bears N.43°E., 35 lks. dist., mkd. 1/4 S5 BT.

A Fir 20" dia., bears S.4°E., 19 lks. dist., mkd. 1/4 S8 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley, crew - May/June 1968 - C.S. File 54/36-179

Found - No trace of corner stone.

20" D.Fir, now snag, S.4°E., 12.5 ft. opened for scribe "8".

18" D.Fir now stump, N.43°E., 23.1 ft.

Set Brass cap at cor. mkd: County Surveyors Office

T 33 S R 7 W

1/4 $\frac{S}{S}$ $\frac{5}{8}$

1968

New BTs -11" D.Fir S.46°E., 47.3 ft. mkd. 1/4 S8 CS BT.

12" D.Fir N.4°E., 152.5 ft. mkd. 1/4 S5 CS BT.