

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 (DCSO records Vol. 21 Page(s) 9047)

 Set a granite stone, 16x10x7 ins., 11" in the ground for cor. to secs. 8, 9, 16 and 17, mkd. with 4 notches on E. and S. edges, and raised a mound of stone, 2 ft. base, 1½ ft. high, W. of cor. Pits impracticable.

Not FD. DCSO JP 6/1968 (added 10/18/2016) - C.S. 54/36-163

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #845, surveyed April/Nov. 1975 (DCSO records Vol. 41 Page(s) 16280-81)

 Point for the cor. of secs., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 33	S R 7	W
	S 8	S 9
	S 17	S 16
1975		

from which

- A Sugar Pine 13" dia., bears N.25°E., 10 lks. dist., mkd. T33S R7W S9 BT.
- A Fir 20" dia., bears S.65°E., 86½ lks. dist., mkd. T33S R7W S16 BT.
- A Fir 25" dia., bears S.1°W., 70½ lks. dist., mkd. T33S R7W S17 BT.
- A Fir 7" dia., bears N.73°W., 63 lks. dist., mkd. T33S R7W S8 BT. This tree also has scribe marks RS 901 BT visible on SW face.

From this point, a point established and recorded by Max W. Hull, L.S. #901, in 1973, bears West, 0.964 chs. dist., monumented with an iron rod, 5/8" dia., firmly set, projecting 4" above ground, with plastic cap mkd. HULL RS 901, from which bearing trees mkd. by Hull

- A Fir 6" dia., bears N.71¼°E., 37½ lks. dist., with scribe marks S9 RS 901 BT visible on partially healed blaze.
- A Madrone 9" dia., bears S.27°E., 17½ lks. dist., with scribe marks S16 RS 901 BT visible on partially healed blaze.
- A Madrone 6" dia., bears S.19 3/4°W., 59 lks. dist., with scribe marks S17 RS 901 BT visible on partially healed blaze.
- A Live Oak 6" dia., bears N.36¼°W., 35½ lks. dist., with scribe marks S8 RS 901 BT visible on partially healed blaze.

cont.

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2739; Surveyed April/May 2014 - (DCSO records Vol. 58 Page(s) 23249)

The cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 2½" dia., firmly set, projecting 10" above the ground, in a collar of stone, with brass cap (properly) mkd.

from which the remains of BTs mkd. by Roseberry & Aanrud in 1975

A burnt fir snag, 31" dia., bears S.65°E., 57.1 ft., with a healed blaze.

A sawed and burnt fir stump, 22" dia., bears N.75½°W., 41.6 ft., with a healed blaze. (Record, N.73°W.)

and new accessories

An iron rod, 24" long, 5/8" dia., set 22" in the center of a sawed and burnt fir stump, 9" dia., 1 ft. high, for a reference monument, bears N.61°39'40"E., 27.50 ft., with aluminum cap, 2" dia., mkd. RM T33S R7W S9 27.50 FT 2014, and an arrow pointing to the cor.

An iron rod, 24" long, 5/8" dia., set 22" in the center of a sawed and burnt fir stump, 11" dia., 1 ft. high, for a reference monument, bears S.10°16'34"E., 14.90 ft., with aluminum cap, 2" dia., mkd. RM T33S R7W S16 14.90 FT 2014, and an arrow pointing to the cor.

From this cor., a point established by Hull, PLS No. 901, in 1973, bears N.87°52'56"W., 63.62 ft (Rec. West), monumented with an iron rod, 5/8" dia., firmly set, projecting 4" above the ground, with a melted plastic cap, and was not utilized during the course of this survey. From which BTs mkd by Hull

A burnt fir snag, 20" dia., bears N.71¼°E., 24.8 ft., no marks visible.

A burnt madrone snag, 10" dia., bears S.27°E., 11.6 ft., no marks visible.

A burnt madrone snag, 14" dia., bears S.19¾°W., 38.9 ft., no marks visible.

A burnt live oak snag, 8" dia., bears N.36¼°W., 23.4 ft., with no marks visible on open double blaze.