

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 (DCSO records Vol. 21 Page(s) 9049-50)

Set a Laurel post, 3 ft. long, 4" sq., 24" in the ground, for corner of secs. 4, 5, 8 and 9, marked T33S S4 on NE.; R7W S9 on SE.; S8 on SW.; and S5 on NW. faces; with 5 notches on S. and 4 notches on E. edges, from which
A Chinquapin 5" dia., bears N.53°E., 19 lks. dist., mkd. T33S R7W S4 BT.
A Chinquapin 5" dia., bears S.44°E., 22 lks. dist., mkd. T33S R7W S9 BT.
A Laurel 4" dia., bears S.42°W., 14 lks. dist., mkd. T33S R7W S8 BT.
A Chinquapin 4" dia., bears N.9°W., 5 lks. dist., mkd. T33S R7W S5 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley, crew - June 4, 1968 - C.S. File 54/36-176

Found - 1½" I.Pipe and old BT (5" Chinquapin), plus 2 other BTs, approx. 15 years old which are unrecorded.
22" S.Pine N.66°W., 31.7 ft., shows scribing of, S
22" D.Fir S.53°E., 26.0 ft., opened and found scribing of S T
Orig. 5" Chinquapin, now 10", N.53°E., 12.5 ft., shows scribing of, T33S R7W S4 BT)

Set Brass cap at cor. mkd: County Surveyors Office
T 33 S R 7 W
S 5 | S 4
S 8 | S 9
1968

Rescribe-10" Chinquapin N.53°E., 12.5 ft. mkd. T33S R7W S4 CS BT.
22" D.Fir S.53°E., 26.0 ft. mkd. T33S R7W S9 CS BT.
New BTs -10" Chinquapin N.67°W., 21.8 ft. mkd. T33S R7W S5 CS BT.
10" Laurel S.39°W., 25.3 ft. mkd. T33S R7W S8 CS BT.
This corner lies on top of small spur.