

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 (DCSO records, Vol. 21 Page 9052)

Set a Fir post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. corner, marked ¼S5 on W. face and 4 on E. face, from which

A Laurel 6" dia., bears N.16°E., 37 lks. dist., marked ¼ S4 BT.

A Laurel 9" dia., bears N.46°W., 22 lks. dist., marked ¼ S5 BT.

Survey by Norman D. Price - For: Dollar and Patterson Lumber Co. - March/Aug. 1954 - C.S. File 41/301

Determined at the record bearing and distance from the original NW. bearing tree.

Set an Iron pipe, 3 ft. long, 1½" dia., 28" in the ground, mkd. RS33; from which the original bearing trees:

A Madrona 13" dia., bears N.46°W., 22 lks. dist., mkd. ¼ S5 BT.

A Madrona 12" dia., dead and down and moved out of position in a skid road, bears N.46°E., 46 lks. dist., mkd. ¼ S4 BT.

SEARCHED FOR, NOT FOUND, DCSO, J.Powell, June 4, 1968, C.S. File 54/36-177

This corner was renewed with iron pipe. Have looked 2 times coming from the north & south. Cor. seems to fall in rd.

David Edwards - Crew: Brant Miller & Eric Sprinkle - 11/8/2013 - C.S. File 65/80-44

Found - 1½" dia., iron pipe.

New - A dead 12" dia., fir bears N.5°E., 19.4 ft. scribed "¼ S4 BT" (corner is in burned area)

A 7' dia., fir bears N.46°W., 38.4 ft. scribed "¼ S5 BT"

Note - Dec. 15¼°E.