

PRIMARY CORNER DESCRIPTION C C for Secs. 4 and 5 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 (DCSO records Vol. 21 Page(s) 9052)

-----  
I set a Pine post, 3 ft. long 4" sq., 24" in the ground, for closing corner of secs. 4 and 5, marked C C T33S R7W on S.; S4 on E.; and S5 on W. faces, with 4 grooves on E. and 2 grooves on W. faces, from which

A Chinquapin 8" dia., bears S.83°E., 134 lks. dist., mkd. T33S R7W S4 BT.

A Yellow Pine 9" dia., bears S.46½°W., 142 lks. dist., mkd. T33S R7W S5 BT.

This corner stands on E. side of ridge, bearing NE. and SW., about 100 ft. above stream.

Survey by Norman D. Price - For: Dollar and Patterson Lumber Co. - March/Aug. 1954 - C.S. File 41/301

-----  
Determined by reference to the measurements from the original bearing trees.

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, mkd. RS33, from which the original bearing trees:

A Chinquapin stub 16" dia., bears S.83°E., 134 lks. dist., on which only axe marks remain.

A Yellow Pine 20" dia., bears S.47½°W., 142 lks. dist., with partial scribe marks visible.

and a new bearing tree

A Sugar Pine 6" dia., bears S.78°E., 25 lks. dist., mkd. T33S R7W S4 CC RS33 BT.

Douglas Co. Surveyors Office - John Powell and Frank Jones - Dec. 12, 1967 - C.S. File 54/36-126

-----  
Found - 2" Iron pipe at sec. cor.

Orig. 9" now 18" Yellow Pine S.47½°W., 93.7 ft. tree opened, scribe visible.

6" S.Pine, now dead, S.78°E., 16.3 ft. scribe visible, T33S R7W S4 CC RS33 BT.

New BT - Chinquapin, S.30°E., 17.3 ft. mkd. T33S R7W S4 CC CS BT.

This corner lies on top of ridge running NE-SW about 60 ft. South of old road intersection.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION CC for secs. 4 & 5 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas Co. Surveyors Office - Randall Smith & Stephen Flause  
- 10/19/95 - C.S. 64/64-5

-----  
Found - 2" O.D. iron pipe protruding 2" above ground with  
a 1" Dia. metal washer in top stamped "RS CC".  
Iron pipe is bent, to is 1' west of plumb.  
9" now 25" Dia. Ponderosa pine with a previously  
opened now healed blaze, bears S.47½°W., 92.5'.  
Orig. Chinquapin BT is gone  
6" now 6" dia. down and rotting pine with scribing  
visible "T33S R7W S4 RS 338 BT" root hole agrees  
with record bearing and distance (S.78°E.,  
16.3').  
1967 DCSO Chinquapin BT now gone a root hole was  
found at rec. brg. & dist. (S.30°E., 17.3')  
Set - 2¾" dia. brass cap on a 1 3/8" O.D. by 32" long  
iron pipe is set at plumb position of found 2"  
I.P. protrudes 3" above ground. Removed 2" I.P.  
measured 35" long is reset along north edge of  
BC/IP protrudes 2" above ground.  
New BTs- 14" dia. D.Fir, double blazed and scribed "T33S R7W  
CC S4 CS BT", bears S.83°E., 15.8'  
13" dia. Pine, double blazed and scribed "T33S R7W  
CC S5 CS BT", bears S.2°W., 25.0'  
15" dia. Chinquapin, double blazed and scribed "T33S  
R7W CC S5 CS BT", bears S.73°W., 54.1'

Ron Quimby - Crew: N. Fromdahl & D. Manring - 9/2014 - C.S.  
File 65/86-21

-----  
Condition report only  
Found - DCSO brass cap.  
17" D.Fir S.83°E., 15.8 ft. good scar.  
16" Pine S.2°W., 25.0 ft. good scar.  
16" Chinquapin S.73°W., 54.1 ft. vis. scribe.  
26" Pine S.47½°W., 92.5 ft. good scribe.  
Note - Area burnt 2013.  
Corner lies on NE SW ridge approx. 60' South of Rd.  
Intersection.  
Compass decl. 15½°E.