

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 329700

PRIMARY CORNER DESCRIPTION S. 1/4 Cor. Sec. 33 only, T32-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Pg 8704)

-----  
Marked a Chinquapin 6" dia., for the ¼ sec. cor. mkd. S C ¼ on N. side, from which

A Cedar 6" dia., bears S.55°W., 26 lks., mkd. S C ¼ S BT.

A Maple 7" dia., bears N.45°W., 6 lks., mkd. SC ¼ S BT.

Survey by Norman D. Price - For: Dollar and Patterson Lumber Co. - March/Aug. 1954 - C.S. File 41/301

-----  
At proportionate distance, there is no remaining evidence of the original corner.

Set an iron pipe 3 ft. long, 1½" dia., 28" in the ground, mkd. RS33, from which

A D.Fir 52" dia., bears N.59½°E., 58 lks. mkd. ¼ S33 SC RS33 BT.

A Red Cedar 24" dia., bears N.42½°W., 115 lks. mkd. ¼ S33 SC RS33 BT.

SEARCHED FOR, NOT FOUND, DCSO, JOHN POWELL, DEC. 1967 C.S. File 54/36-127

Survey by Richard Templin for Arlie Land & Cattle Co. & J-S Investments, July 1995 - M122-53

-----  
Found - A sawed stump, 55 inch diameter bears record N.59½°E., 58 lks. (38.28 ft.) with scribe visible.

Set - 5/8" x 30" iron rod with a yellow plastic cap marked "TEMPLIN LS 2359"

New Accessories -

D.Fir, 10" dia. bears N.83°E. 23.3 ft. scribed "S¼ S33 BT"

Forked Ash, 8" dia. bears S.53°E., 6.5 ft. scribed "S¼ S33 BT"

Ash, 12" dia. bears S.72°W., 30.1 ft. scribed "S¼ S33 BT"

Ash, 12" dia. bears West, 25.9 ft. scribed "S¼ S33 BT"

Ron Quimby - Crew: N. Fromdahl & D. Manring - 9/2014 - C.S. File 65/86-17

-----  
Found - 5/8" I.Rod Templin cap.  
55" stump bears rec. N.59½°E., 38.3 ft. vis. scribe.  
10" D.Fir N.83°E., 23.3 ft. good scar.  
14" maple (rec. Ash) S.53°E., 6.5 ft. good scar.

New - 24" Maple N.53°W., 61.6 ft. scribe ¼ S33 BT.

Note - Area badly burnt 2013  
Compass decl. 15½°E.