

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 (DCSO records Vol. 21 Page(s) 9048)

Set a granite stone, 16x8x8 ins., 11" in the ground, for 1/4 sec. cor. mkd. 1/4 on N. face, from which

A Laurel 6" dia., bears S.28°E., 15 lks. dist., mkd. 1/4 S16 BT.

A Laurel 8" dia., bears N.73°W., 16 lks. dist., mkd. 1/4 S9 BT.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #845, surveyed April/Nov. 1975 (DCSO records Vol. 41 Page(s) 16282)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 26 ins. in the ground, with brass cap marked T 33 S R 7 W

1/4 $\frac{S 9}{S 16}$
1975

from which

A Cedar 20" dia., bears N.26°W., 7 1/2 lks. dist., mkd. 1/4 S9 BT. This tree also has scribe marks RS 901 BT visible on SW. face.

A Sugar Pine 8" dia., bears S.40°W., 160 lks. dist., mkd. 1/4 S16 BT.

From this point, a point established and recorded by Max W. Hull, L.S. #901 in 1973, bears S.87°26'W., 0.48 chs. dist., monumented with an iron rod, 5/8" dia., firmly set, projecting 6" above ground, with plastic cap mkd. HULL RS 901, from which bearing trees mkd. by Hull:

A Cedar 20" dia., bears N.79°E., 45 1/2 lks. dist., with scribe marks RS 901 BT visible on partially healed blaze.

A Fir 20" dia., bears S.15°E., 82 lks. dist., with scribe marks RS 901 BT visible on partially healed blaze.