

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 (DCSO records Vol. 21 Page(s) 9051)

-----  
Set a Fir post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. corner, marked ¼ S4 on N.; and 9 on S. face, from which  
A Cedar 5" dia., bears N.71½°E., 18 lks. dist., mkd. ¼ S4 BT.

A Cedar 4" dia., bears S.4°E., 29 lks. dist., mkd. ¼ S9 BT.

This corner stands 225 ft. above stream.

Survey by Norman D. Price - For: Dollar and Patterson Lumber Co. - March/Aug. 1954 - C.S. File 41/301

-----  
Determined at the record bearing and distance from the original SE bearing tree.

Set an Iron pipe, 3 ft. long, 1½" dia., 28" in the ground, mkd. RS33, from which the only extant original bearing tree:

An Incense Cedar 8" dia., bears S.4°E., 29 lks. dist., mkd. ¼ S9 BT.

And a new bearing tree:

An Incense Cedar 14" dia., bears N.74¼°E., 46 lks. dist., mkd. ¼ S4 RS33 BT.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 4/22/2025 - C.S. File 67/60-23

-----  
Found - 1½" Iron pipe projecting 8"  
Burned - dead 28" cedar N.74¼°E. 30.4 ft (Rec 46 lks) fully healed single blaze.

New - 5/8"x30" Iron rod with D.C.S.O. plastic cap N.54°E. 53.8 ft up 2"

5/8"x30" Iron rod with D.C.S.O. plastic cap N.6°W. 32.0 ft

Notes - Mon. is approx. 50' S. of a gravel rd in dense brush  
Mon. is near top of moderate S.E. slope that form westerly wall of shallow draw.

Compass decl. 14½°E.

OCRS COORDINATE SYSTEM

COTTAGE GROVE-CANYONVILLE ZONE

N 39665.114 E 110481.865