

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 9041)

Set a Laurel post, 4 ft. long, 4" sq., 2 ft. in the ground, mkd. T33S R7W S10 on NE.; S15 on SE.; S16 on SW.; and S9 on NW. faces; also 4 notches on S. and 3 notches on E. angles of same for the cor. to secs. 9, 10, 15 and 16, from which

- A Laurel 12" dia., bears N.50°E., 15 lks. dist., mkd. T33S R7W S10 BT.
- A Laurel 5" dia., bears S.22°E., 44 lks. dist., mkd. T33S R7W S15 BT.
- A Fir 46" dia., bears S.10°W., 28 lks. dist., mkd. T33S R7W S16 BT.
- A Laurel 8" dia., bears N.12°W., 40 lks. dist., mkd. T33S R7W S9 BT.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 (DCSO records Vol. 21 Page(s) 9048)

The Sec. cor. of secs. 9, 10, 15 and 16, which having disappeared, I restore the cor. by setting a Fir post, 3 ft. long, 4" sq., 24" in the ground, mkd. T33S S10 on NE.; R7W S15 on SE.; S16 on SW.; and S9 on NW.; faces, with 4 notches on S. and 3 notches on E. edges, and witnessed as described by the Surveyor General.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley, crew - April 3, 1968 - C.S. File 54/36-167

Found - Orig. 12" now 17" Laurel N.50°E., 9.9 ft. opened for scribe "BT"
 Orig. 46" now 52" D.Fir S.10°W., 18.5 ft., no marks visible.

No trace of SE or NW BTs.

Set Brass cap at cor. mkd: County Surveyors Office

Doug. Co.
 T 33 S R 7 W
 S 9 | S 10
 S 16 | S 15
 Jos. Co.
 1968

New BTs -14" D.Fir N.78½°W., 16.2 ft. mkd. T33S R7W S9 CS BT
 15" D.Fir N.53°E., 17.6 ft. mkd. T33S R7W S10 CS BT
 7" B.Oak S.8½°E., 28.7 ft. mkd. T33S R7W S15 CS BT

Reblaze and rescribe:

(Cont. Next Page)

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

52" D.Fir S.10°W., 18.5 ft. mkd. T33S R7W S16 CS BT
Added 10/16/2016
Also found
44" D.Fir facing SW from cor.? Bark scribe faint CC T3 R7W
28" D.Fir facing west from cor. scribed in wood "S"
visible. This tree opened - scribe quite old.
This cor. approx. 250-300 ft. north of 9|10/16|15
See BLM letter in C.S. file.

Cor. Fd. and used in BLM resurvey by Roseberry and Aanrud,
under Group #845, surveyed April/Nov. 1975 (DCSO records,
Vol. 41 Pages 16281-82)

BLM resurvey by Rollin D. Aanrud and Lynn M. Roseberry,
Cadastral Surveyors, under Group #1050, surveyed May/Sept.
1981 (DCSO records Vol. 45 Page(s) 17417)

The Sec. cor., perpetuated and recorded by DCSO in 1968,
monumented with an iron post, 1" dia., firmly set, projecting
12" above ground with 1968 brass cap
from which the remains of the original bearing trees
A Madrone 18" dia., bears N.50°E., 15 lks. dist., with
healed blaze.
A sawed Fir stump 52" dia., bears S.10°W., 28 lks. dist.,
no marks visible. This tree was remarked by the DCSO,
and the blaze is healed.
and bearing trees mkd. by the County Surveyors Office
A Fir 20" dia., bears N.53°E., 26½ lks. dist., with healed
blaze.
A B.Oak 8" dia., bears S.8½°E., 45 lks. dist., with healed
blaze.
A Fir 22" dia., bears N.78½°W., 24½ lks. dist., with
healed blaze.
and a new bearing tree
A Madrone 7" dia., bears S.9½°W., 46½ lks. dist., mkd.
T33S R7W S16 BT.

Gerald Nygren - For: Plum Creek Timberlands, LP - March 2014
- M167-56

Found - Douglas Co. Surveyors Brass cap in record position.
BTs are burnt dead snags.