

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Pg 9042)

-----  
Set a Laurel post, 3 ft. long, 3" dia., 2 ft. in the ground, mkd. ¼ S on W. side for the ¼ sec. cor., from which  
A Fir 22" dia., bears N.35°E., 20 lks. mkd. ¼ S BT.  
A Laurel 12" dia., bears N.30°W., 130 lks., mkd. ¼ S BT.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #1050, surveyed May/Sept. 1981 (DCSO records Vol. 45 Page(s) 17417-18)

-----  
The ¼ sec. cor., determined at record bearing and distance from the original bearing trees

A Fir 32" dia., bears N.35°E., 20 lks. dist., no marks visible on opened pitched over blaze.

A Madrona 18" dia., bears N.30°W., 130 lks. dist., no marks visible on opened, decayed, double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 20 ins. in the ground, with brass cap marked

T 33 S R 7 W  
¼  
S 9 | S 10  
1981

from which new bearing trees

A Sugar Pine 21" dia., bears N.38 3/4°E., 67 lks mkd ¼ S10 BT

A Fir 12" dia., bears N.47½°W., 54½ lks., mkd. ¼ S9 BT.

FD. OK by Lloyd Smith, 3/85, M 98-47

Ron Quimby - Crew: J. Leonard and N. Fromdahl - 4/2014 - C.S. File 65/82-27

-----  
Found - BLM brass cap  
38" 4'tall fir stump badly burnt N.35°E., 13.4 ft.  
12" burnt pine stump N.39°E., 44.7 ft.  
20" madrona N.30°W., 86.7 ft. good scar.  
18" fir N.47°W., 36.3 ft. good scar.

Note - Area badly burnt 8/2013  
Compass decl. 15½°E.

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2739; Surveyed April/May 2014 - (DCSO records Vol. 58 Page(s) 23254)

-----  
The ¼ sec. cor. of secs. 9 & 10, monumented with an iron post, 2½" dia., firmly set, projecting 9" above the ground, with brass cap (properly) mkd. continued next pg

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of original bearing trees  
A burnt and rotted fir stump, 33" dia., bears N.35°E.,  
13.2 ft., no marks visible.  
A burnt madrone snag, 19" dia., bears N.30°W., 85.8 ft.,  
no marks visible.  
and the remains of BTs mkd. by Aanrud and Roseberry in 1981  
A fir, 19" dia., bears N.47½°W., 36.0 ft., with a healed  
blaze.  
and a new accessory  
An iron rod, 24" long, 5/8 in. diam., set 22" in the ground  
for a reference monument, bears N.49°41'44"E., 22.40  
ft., with aluminum cap, 2" dia., mkd. RM ¼ S10 22.40 FT  
2014, and an arrow pointing to the cor.