

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 9042-43)

-----  
Set a Laurel post, 4 ft. long, 4" sq., 2 ft. in the ground, mkd. T33S R7W S3 on NE.; S10 on SE.; S9 on SW.; and S4 on NW. faces, also 5 notches on the S. and 3 on the E. angles of same for the cor. to secs. 3, 4, 9 and 10, from which  
A Laurel 8" dia., bears N.66°E., 35 lks. dist., mkd. T33S R7W S3 BT.  
A Laurel 10" dia., bears S.76°E., 65 lks. dist., mkd. T33S R7W S10 BT.  
A Laurel 8" dia., bears S.65°W., 49 lks. dist., mkd. T33S R7W S9 BT.  
A Fir 14" dia., bears N.80°W., 10 lks. dist., mkd. T33S R7W S4 BT.

Survey by Norman D. Price - For: Dollar and Patterson Lumber Co. - March/Aug. 1954 - C.S. File 41/301

-----  
Set an Iron post, 3 ft. long, 2" dia., 28" in the ground, mkd. RS 33,  
from which the only extant original bearing tree:  
A D.Fir 26" dia., bears N.80°W., 10 lks. dist., mkd. T33S R7W S4 with BT blaze healed.  
and new bearing trees:  
A Madrona 7" dia., bears S.88°E., 44 lks. dist., mkd. T33S R7W S10 RS33 BT.  
A Live Oak 7" dia., bears S.26°W., 27 lks. dist., mkd. T33S R7W S9 RS33 BT.  
A Madrona 8" dia., bears N.47°E., 64 lks. dist., mkd. T33S R7W S3 RS33 BT.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #845, surveyed April/Nov. 1975 (DCSO records Vol. 41 Page(s) 16275-76)

-----  
The Sec. Cor., perpetuated and recorded by Price in 1954, monumented with an iron pipe, 2" dia., firmly set, projecting 4" above ground, from which the remaining original bearing tree:  
A Fir 35" dia., bears N.80°W., 10 lks. dist., with scribe mark S and other illegible scribe marks visible on opened blaze.  
and the remains of bearing trees mkd. by Price  
A Madrone snag 8" dia., bears N.47°E., 64 lks. dist., with scribe marks T33S R7W S3 RS33 BT visible on open blaze.  
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A root hole bears S.88°E., 44 lks. dist., with a down Madrone alongside, 7" dia., with scribe marks T33S R7W S10 RS33 BT visible on open blaze.

A root hole bears S.26°W., 27 lks. dist., with a down Live Oak alongside 7" dia., with scribe marks T33S R7W S9 RS33 visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, directly over iron pipe, with brass cap marked

T 33 S R 7 W  
S 4 S 3  
S 9 S 10  
1975

from which new bearing trees

A Tan Oak 7" dia., bears S.46¼°E., 40 lks. dist., mkd. T33S R7W S10 BT.

A Fir 23" dia., bears S.49½°W., 91 lks. dist., mkd. T33S R7W S9 BT.

No other suitable trees available within limits.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #1050, surveyed May/Sept. 1981 (DCSO records Vol. 45 Page(s) 17418-19)

The sec. cor., monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with 1975 brass cap.

from which the remaining original bearing tree

A Fir 36" dia., bears N.80°W., 10 lks. dist., with illegible scribe marks visible on a burned blaze.

and the remains of a bearing tree mkd. by Price and described in the 1975 resurvey record

A root hole bears S.26°W., 27 lks. dist., alongside of which is lying a shattered live Oak size indeterminate, w/scribe mks T33S R7W S9R S33 BT vis. on an open blaze.

and bearing trees mkd. by Aanrud and Roseberry

A TanOak snag, 7" dia., bears S.46¼°E., 40 lks. dist., no marks visible on partly healed blaze.

A Fir 25" dia., bears S.43½°W., 91 lks. dist., with scribe mrks T33S R7W S9 BT vis. on open blaze. (Rec. S.49½°W.)

and new bearing trees

A Madrone 6" dia., bears N.45°E., 66½ lks. dist., mkd. T33S R7W S3 BT.

A Madrone 6" dia., bears S.11°E., 44½ lks. dist., mkd. T33S R7W S10 BT.

FD. OK by Lloyd Smith, 3/85, M 98-47

