

PRIMARY CORNER DESCRIPTION C.C. for 3 and 4 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 9044)

Set a Chinquapin post, 4 ft. long, 4" sq., mkd. T33S R7W on S. side, S3 and 3 notches on E. side, S4 and 3 notches on W. and T32S R7W S34 on N. faces of same for closing cor. bet. secs. 3 and 4, from which

A Fir 38" dia., bears S.20°E., 14 lks. dist. mkd. T33S R7W S3 BT.

A Fir 24" dia., bears S.4°W., 16 lks. dist. mkd. T33S R7W S4 BT.

A Fir 40" dia., bears N.34°W., 22 lks. dist. mkd. T32S R7W S34 BT.

Survey by Norman D. Price - For: Dollar and Patterson Lumber Co. - March/August 1954 - C.S. File 41/301

There is no remaining evidence of the original closing corner.

Set an iron pipe 3 ft. long, 2" dia., 28" in the ground, mkd. RS33. from which

A D.Fir 30" dia., bears S.47¼°E., 98 lks. dist., mkd. T33S R7W S3 CC RS33 BT.

A Chinquapin 10" dia., bears S.20°W., 114 lks. dist., mkd. T33S R7W S4 CC RS33 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W Penley, crew - March 1968 - C.S. File 54/36-181

Found - 2" I.Pipe at sec. corner.

30" D.Fir S.47°E., 64.7 ft. shows scar.

10" Chinquapin, now dead, S.20°W., 25.2 ft., scribe visible, T33S R7W S4 CC BT

New BT - 9" D.Fir S.28°W., 28.2 ft. mkd. T33S R7W S4 CC CS BT.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #845, surveyed April/Nov. 1975 (DCSO records Vol. 41 Page(s) 16277-78)

True point for the closing cor. of secs. 3 and 4.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

(Cont. Next Page)

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION C.C. for Secs. 3 and 4 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

T 32 S R 7 W
S 34
S 4 | S 3
C C
T 33 S R 7 W
1975

from which the remains of bearing trees mkd. by Price
A Fir 42" dia., bears S.51¼°E., 80 lks. dist. with healed
blaze.
A Chinquapin snag 11" dia., bears S.21½°W., 106 lks.
dist., with scribe marks T33S R7W RS33 CC BT visible on
open blaze.
A Chinquapin snag 6" dia., bears N.27°W., 34½ lks. dist.,
with scribe marks T32S R7W S34 RS33 CC BT visible on
open blaze.
and a bearing tree mkd. by Powell in 1968
A Fir 9" dia., bears S.34°W., 36 lks. dist., with healed
blaze.

From this point, the closing cor. of secs. 3 and 4,
established by Price in 1954, bears N.0°05'E., 0.08 chs.
dist., monumented with an iron pipe, 2" dia., firmly set,
projecting 6" above ground, with brass washer mkd. RS33 from
which the remains of bearing trees mkd. by Price:
A Fir 42" dia., bears S.47¼°E., 85 lks. dist., with healed
blaze.
A Chinquapin snag 11" dia., bears S.20°W., 114 lks. dist.,
with scribe marks T33S R7W S4 RS33 CC BT visible on
open blaze.
A Chinquapin snag 6" dia., bears N.35°W., 27½ lks. dist.,
with scribe marks T32S R7W S34 RS33 CC BT visible on
open blaze.
and a bearing tree mkd. by Powell in 1968
A Fir 9" dia., bears S.28°W., 43 lks. dist. with healed
blaze.

This point now becomes an amended monument.