

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Pg 9042)

-----  
Marked a Chinquapin 10" dia., ¼ S on W. side, for ¼ sec. cor., from which

A Chinquapin 5" dia., bears S.72°E., 42 lks. dist., marked ¼ S BT.

A Fir 40" dia., bears N.33°W., 20 lks. dist., mkd. ¼ S BT.

-----  
Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley, crew - April 1, 1968 - C.S. File 54/36-170

-----  
Found - Orig. 40" now 48" D.Fir N.33°W., 13.2 ft. faint bark scribed ¼ S BT.

No trace of Chinquapin corner tree or SE BT.

Set Brass cap at cor. mkd: County Surveyors Office

T 33 S R 7 W

¼  $\frac{S\ 10}{S\ 15}$  Doug. Co.  
Jos. Co.

1968

New BT - 20" D.Fir S.60°W., 74.3 ft. mkd. ¼ S15 CS BT.

Reblaze and Rescribe:

48" D.Fir N.33°W., 13.2 ft. mkd. ¼ S10 CS BT.

-----  
Cor. Fd. and used in BLM resurvey by Aanrud and Roseberry under Group #1050, surveyed May/Sept. 1981 (DCSO records, Vol. 45 Page 17416)

-----  
FD. OK by Lloyd Smith, 3/85, M 98-47

-----  
Gerald Nygren - For: Plum Creek Timberlands, LP - March 2014 - M167-56

-----  
Found - Douglas Co. Surveyors Brass cap in record position. BT is burnt dead snag.

-----  
BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2739; Surveyed April/May 2014 - (DCSO records Vol. 58 Page(s) 23246)

-----  
The ¼ sec. cor. of secs. 10 and 15, monumented with an iron post, 1" dia., firmly set, projecting 9" above the ground, with brass cap (properly) mkd.

from which the remains of an original bearing tree

A sawed and burnt fir stump, 55" dia., bears N.33°W., 15.8 ft., no marks visible.

and the remains of BTs mkd. by the Douglas Co Surveyor's Office in 1968

continued next page

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A burnt and broken fir stump, 16" dia., bears S.58°W.,  
74.3 ft., no marks visible.

and new accessories

An iron rod, 30" long, 5/8" dia., set 28" in the ground for  
a reference monument, bears N.50°32'33"E., 26.60 ft.,  
with aluminum cap, 2" dia., mkd. RM ¼ S10 26.60 FT  
2014, and an arrow pointing to the cor.

An iron rod, 30" long, 5/8" dia., set 28" in the ground for  
a reference monument, bears S.43°41'23"E., 21.60 ft.,  
with aluminum cap, 2" dia., mkd. RM ¼ S15 21.60 FT  
2014, and an arrow pointing to the cor.