

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 440540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Lloyd D. Smith - For: State of Oregon Dept. of Forestry - March 5, 1985 - M 98-47

-----  
Set Oregon State Dept. of Forestry 1½" x 36" alum. pipe with 3 3/4" alum. cap and magnetic insert, 30" in the ground.  
BTs - 4" Fir bears S.15°E., 7.5 ft. with bearing tree tag.  
4" Fir bears S.71°W., 9.6 ft. with bearing tree tag.

Gerald Nygren - For: Plum Creek Timberlands, LP - March 2014 - M167-56

-----  
Found - State Forestry alum. cap set per M98-47 in record position.  
BTs are burnt dead snags.

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2739; Surveyed April/May 2014 - (DCSO records Vol. 58 Page(s) 23250-1)

-----  
The center ¼ sec. cor. of sec. 10, established by Smith, in 1985, and is accepted as the cor.; monumented with an Oregon State Department of Forestry aluminum post, 1½" dia., firmly set, projecting 2" above the ground, with aluminum cap (properly) mkd.  
from which the remains of bearing trees mkd. by Smith  
A burnt fir snag, 13" dia., bears S.15½°E., 8.6 ft., with a healed blaze.  
A burnt fir snag, 14" dia., bears S.70¾°W., 10.1 ft., with a healed blaze.  
and new accessories  
An iron rod, 24" long, 5/8" dia., set 22" in the ground for a reference monument, bears S.46°22'01"W., 26.00 ft., with aluminum cap, 2" dia., mkd. RM C¼ S10 26.00 FT 2014, and an arrow pointing to the cor.  
An iron rod, 24" long, 5/8" dia., set 22" in the ground for a reference monument, bears N.5°52'30"W., 24.30 ft., with aluminum cap, 2" dia., mkd. RM C¼ S10 24.30 FT 2014, and an arrow pointing to the cor.