

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Pg 9043)

Set a Laurel post 3 ft. long, 4" sq., 18" in the ground, for the ¼ sec. cor. mkd. ¼ sec. on N. from which
A S.Pine 48" dia., bears North, 48 lks. dist., mkd. ¼ S BT
A Fir 44" dia., bears S.3°W., 13 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley, crew - May/June 1968 - C.S. File 54/36-174

Found - 44" D.Fir now 50" snag top, S.3°W., 8.6 ft. bark scribe visible.
48" now 52" S.Pine, North, 31.7 ft., no marks visible.

Set Brass cap at cor. mkd: County Surveyors Office
T 33 S R 7 W
¼ $\frac{S \ 3}{S \ 10}$
1968

Reblaze and rescribe:
52" S.Pine North, 31.7 ft. mkd. ¼ S3 CS BT.
New BT - 7" Tan Oak S.46°E., 29.1 ft. mkd. ¼ S10 CS BT.

Cor. Fd. and used in BLM resurvey by Roseberry and Aanrud, under Group #845, surveyed April/Nov. 1975 (DCSO records, Vol. 41 Pages 16274-75)

FD. OK by Lloyd Smith, 3/85, M 98-47

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2739; Surveyed April/May 2014 - (DCSO records Vol. 58 Page(s) 23251-2)

The ¼ sec. cor. of secs. 3 and 10, monumented with an iron post, 1" dia., firmly set, projecting 12" above the ground, with brass cap (properly) mkd.

from which the remains of original bearing trees

A burnt sugar pine snag, 41" dia., bears North, 31.7 ft., no marks visible.

A burnt and sawed fir stump, 49" dia., bears S.3°W., 8.6 ft., with a rotted and burnt face, no marks visible.

and new accessories

An iron rod, 24" long, 5/8" dia., set 22" in the ground for a reference monument, bears S.51°55'07"W., 21.40 ft., with aluminum cap, 2" dia., mkd. RM ¼ S10 21.40 FT 2014, and an arrow pointing to the cor.

continued next page

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

An iron rod, 24" long, 5/8" dia., set 22" in the ground for a reference monument, bears N.24°57'31"W., 21.60 ft., with aluminum cap, 2" dia., mkd. RM ¼ S3 21.60 FT 2014, and an arrow pointing to the cor.