

PRIMARY CORNER DESCRIPTION C.C. cor. for Secs. 34 & 35 only, T32-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8702)

Set a Fir post 4½ ft. long, 4" sq., 20" in the ground, for the S. cor. to Secs. 34 and 35 marked S C T32S R7W on N.; S35 on E.; and S34 on W., from which
A Fir 14" dia., bears N.30°E., 43 lks. dist. mkd. S C T32S R7W S35 BT.
A Laurel 10" dia., bears N.26°W., 30 lks. dist. mkd. S C T32S R7W S34 BT.
A Fir 40" dia., bears S.72°W., 47 lks. dist. mkd. S C T33S R7W S3 BT.

Survey by Norman D. Price - For: Dollar and Patterson Lumber Co. - March/Aug. 1954 - C.S. File 41/301

Determined at record bearing and distance from the remains of original SW and NW bearing trees. No evidence of original NE bearing tree found.
At the corner point, which is located in an old E and W fence line, and on old E. and W. blazed line,
Set an Iron pipe, 3 ft. long, 2" dia., 28" in the ground, mkd. RS 33, from which the original bearing trees:
A badly burnt and decayed Fir stump bears S.72°W., 47 lks. dist., on which no marks remain.
A Madrona stool bears N.26°W., 30 lks. dist., on which no marks remain.
And new bearing trees:
A D.Fir 6" dia., bears N.9¼°E., 68 lks. dist., mkd. T32S R7W S35 SC RS33 BT.
A Madrona 12" dia., bears N.24 ¾°W., 27½ lks. dist., mkd. on bark T32S R7W S34 SC RS33 BT.
The geographic position of this cor. is lat. 42°44'24"N., and long. 123°30'10"W.

Fd. OK, DCSO, J.Powell, Dec. 18, 1967, C.S. File 54/36-125

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #845, surveyed April/Nov. 1975 (DCSO records Vol. 41 Page(s) 16268)

The Standard cor. of secs. 34 and 35, perpetuated and recorded by Price in 1954, from the original bearing trees which are no longer in existence, monumented with an iron pipe, 2" dia., firmly set, projecting 6" above ground, with brass cap washer mkd. RS 33, from which bearing trees mkd. by Price:
(Cont. Next Page)

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 469700

PRIMARY CORNER DESCRIPTION S C for Secs. 34 and 35 only, T32-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 11" dia., bears N.9¼°E., 68 lks., with healed blaze.
A Madrone 15" dia., bears N.24 3/4°W., 27½ lks. dist.,
with scribe marks T32S R7W S34 SC RS33 BT visible on
bark blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in
the ground, directly over iron pipe, with brass cap marked

S C
T 32 S R 7 W
S 34 | S 35
1975

Corner is located in a fence line, fence extends E. and W.

BLM resurvey by Terrence O. Nickerson, Cadastral Surveyor and
Gordon L. Caster, Technician, under Group #1528, surveyed
March/April 1990 (DCSO records Vol. 50 Page(s) 18988)

The standard cor. of secs. 34 and 35, monumented with an iron
post, 2½ ins. diam., firmly set, projecting 6 ins. above the
ground, with brass cap mkd.

S C
T 32 S R 7 W
S 34 | S 35
1975

from which the remains of the bearing trees mkd. by Norman D.
Price, Registered Land Surveyor No. 33, recorded in Douglas
County Survey No. 41-301, in 1954

A sawed fir stump, 15 ins. diam., bears N. 9¼° E.,
68 lks. dist., with bottom portion of healed blaze.

A madrone, 16 ins. diam., bears N. 24¾° W., 27½ lks.
dist., with healed blaze.

and a new bearing tree

A fir, 10 ins. diam., bears N. 29¾° E., 64½ lks. dist.,
mkd. T32S R7W S35 SC BT.

Mark Smalley, Roseburg Forest Products - 11/7/1996 - C.S.
65/15-13

Mon. Fd.- 2½" I.P. & B.C.

Bt's Fd.- 15" Fir stump, bears N.9¼°E., 68 lks. still a
stump.

17" Madrone, bears N.24¾°W., 27½ lks. good
healed face.

12" Fir, bears N.29¾°E., 64½ lks. good healed
face.

(Cont. Next page)

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 469700

PRIMARY CORNER DESCRIPTION C.C. cor for Secs. 34 & 35 only, T32-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New Accessories -

14" Fir, bears N.48°W., 9' scribed "S34 BT"

9" Fir, bears N.80°E., 13' scribed "S35 BT"

Found ok by K.DeGroot - 4/1998 - M128-50

Fd. Ok by N. Hibbs, 12/2013 - M166-5A&B