

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Pg 9035)

-----  
Set a Fir post, 4 ft. long, 4" sq., 2 ft. in the ground, marked T33S R7W S11 on NE.; S14 on the SE.; S15 on the SW.; and S10 on NW. faces, also 4 notches on S. and 2 on E. angles of same for the cor. to secs. 10, 11, 14 and 15, from which  
An Alder 16" dia., bears N.52°E., 103 lks. dist., mkd. T33S R7W S11 BT.

A Laurel 9" dia., bears S.74°E., 34 lks. dist., mkd. T33S R7W S14 BT.

A Fir 24" dia., bears S.42°W., 17 lks. dist., mkd. T33S R7W S15 BT.

A Fir 14" dia., bears N.9°W., 43 lks. dist., mkd. T33S R7W S10 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley, crew - March 1968 - C.S. File 54/36-164

-----  
Found - Orig. 24" D.Fir now 52", and down, S.42°W., 11.2 ft., no scar visible.

Orig. 14" now 48" D.Fir N.9°W., 28.4 ft., old axe work visible.

Orig. 9" Laurel, now down and dead, S.74°E., 22.4 ft., found scribe "BT"

No trace of NE Alder BT.

Set Brass cap at cor. mkd: County Surveyors Office

T 33 S R 7 W

S 10 | S 11

S 15 | S 14

1968

New BTs -9" Maple N.67°E., 21.8 ft. mkd. T33S R7W S11 CSBT.

22" D.Fir S.55°W., 32.7 ft. mkd. T33S R7W S15 CS BT.

Reblaze and rescribe:

48" D.Fir N.9°W., 28.4 ft. mkd. T33S R7W S10 CS BT.

No trees in SE quadrant to scribe.

Cor. Fd. and used in BLM resurvey by Aanrud and Roseberry under Group #1050, surveyed May/Sept. 1981 - (DCSO records Vol. 45 Page(s) 17413)

Gerald Nygren - For: Plum Creek Timberlands, LP - March 2014 - M167-56

-----  
Found - Douglas Co. Surveyors Brass cap in record position. BTs are burnt dead snags.

continued next page

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2739; Surveyed April/May 2014 - (DCSO records Vol. 58 Page(s) 23245-6)

-----  
The cor. of secs. 10, 11, 14, & 15, monumented with an iron post, 1" dia., firmly set, projecting 12" above the ground, with brass cap (properly) mkd.

from which an original bearing tree  
A burnt fir snag, 54" dia., bears N.9°W., 28.4 ft., with a healed blaze.

and BTs mkd. by the Douglas Co. Surveyor's Office in 1968  
A maple, 17" dia., bears N.67°E., 21.8 ft., with scribe marks CS visible on partially healed upper blaze and S visible on partially healed lower blaze.

A burnt fir, 37" dia., bears S.55°W., 32.7 ft., with a healed blaze.  
and a bearing tree mkd. by person(s) unknown

A burnt chinquapin, 14" dia., bears S.27¼°E., 21.5 ft., with scribe marks CS visible on partially healed upper blaze & S14 BT visible on partially healed lower blaze.  
No suitable trees available in section 10.

NAD 1983 (2011)  
Latitude: 42°42'33.11"N Longitude: 123°30'14.22"W