

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO recs Vol 21 Pgs 9036-37)

Set a Chinquapin post, 40" long, 20" in the ground, 4" sq., mkd. $\frac{1}{4}$ S on W. side, for the $\frac{1}{4}$ sec. corner, from which
A Laurel 8" dia., bears S.2°E., 22 lks., mkd. $\frac{1}{4}$ S BT
A Chinquapin 8" dia., bears N.44°W., 34 lks. mkd. $\frac{1}{4}$ S BT.

Not fd DCSO JP 3/1968 (added 10/2016) C.S. 54/36-165

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #1050, surveyed May/Sept. 1981 (DCSO records Vol. 45 Page(s) 17413-14)

Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 33 S R 7 W

$\frac{1}{4}$

S 10 | S 11

1981

from which

A Fir 38" dia., bears N.75 $\frac{1}{2}$ °E., 55 lks., mkd. $\frac{1}{4}$ S11 BT.

A Fir 7" dia., bears S.72 $\frac{1}{2}$ °W., 64 $\frac{1}{2}$ lks., mkd. $\frac{1}{4}$ S10 BT.

FD. OK by Lloyd Smith, 3/85, M 98-47

Gerald Nygren - For: Plum Creek Timberlands, LP - March 2014 - M167-56

Found - BLM Brass cap in record position.
BTs of record are burnt dead snags.

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2739; Surveyed April/May 2014 - (DCSO records Vol. 58 Page(s) 23252)

The $\frac{1}{4}$ sec. cor. of secs. 10 and 11, monumented with an iron post, 2 $\frac{1}{2}$ " dia., firmly set, projecting 5" above the ground, with brass cap (properly) mkd.

from which the remains of a BT mkd. by BLM during an administrative survey, in 1978

A burnt madrone snag, 14" dia., bears S.57 $\frac{3}{4}$ °E., 11.7 ft., with a healed blaze.

and the remains of BTs mkd. by Aanrud and Roseberry in 1981

A burnt fir snag, 20" dia., bears S.72 $\frac{1}{2}$ °W., 42.6 ft., with a healed blaze.

continued next page

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

and new accessories

An iron rod, 24" long, $\frac{5}{8}$ " dia., set 22" in the ground for a reference monument, bears N. $82^{\circ}01'14''$ E., 24.00 ft., with aluminum cap, 2" dia., mkd. RM $\frac{1}{4}$ S11 24.00 FT 2014, and an arrow pointing to the cor.

An iron rod, 24" long, $\frac{5}{8}$ " dia., set 21" in the ground for a reference monument, bears S. $24^{\circ}27'20''$ W., 18.90 ft., with aluminum cap, 2" dia., mkd. RM $\frac{1}{4}$ S10 18.90 FT 2014, and an arrow pointing to the cor.