

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 9038)

Set a Fir post, 40" long, 4" sq., 20" in the ground, mkd. ¼ S on W. for the ¼ sec. corner, from which
A Fir 40" dia., bears S.40°E., 47 lks. dist., mkd. ¼ S BT.
A Fir 10" dia., bears N.33°W., 30 lks. dist., mkd. ¼ S BT.

Survey by H. W. Lawrence - For: R. Hissong - Sept. 27, 1967 -C.S. File 55/9-2

Found - Orig. 10" Fir bears N.33°W., 38 lks. mkd. ¼ S BT.
Tree rotted, ring of bark in place, scribed wood nearby.
Orig. 40" Fir now a rotten stump, bears S.40°E., 47 lks., mkd. ¼ S BT.
Set 3/4" O.D. Iron pipe, 36" long, driven 30" into ground, cap marked ¼ S 1543.
New BTs -12" Madrone bears N.45°E., 21.6 ft. mkd. ¼ S2 BT 1543.
10" Chinquapin bears S.44°W., 26.6 ft. mkd. ¼ S3 BT 1543.

Fd. OK, DCSO, J. Powell, March 12, 1968, C.S. File 54/36-178
Fd OK, DCSO, G Langlitz, 9/23/1976, C.S. File 59/24-17

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #845, surveyed April/Nov. 1975 (DCSO records Vol. 41 Page(s) 16271-72)

The ¼ sec. cor., perpetuated and recorded by Lawrence in 1967 monumented with an iron pipe 3/4" dia., firmly set, projecting 4" above ground, with metal tag mkd. ¼ S 1543, from which the remains of the original bearing trees:

A sawed and decayed Fir stump 40" dia., bears S.40°E., 47 lks. dist., no marks visible.

A root hole bears N.33°W., 38 lks. dist., with a down and decayed Fir alongside, size indeterminate, with scribe mark S visible on open blaze.

and bearing trees mkd. by Lawrence

A Madrone 13" dia., bears N.42°E., 33 lks. dist., with scribe marks ¼ S2 BT 1543 visible on partially healed blaze.

A Chinquapin 12" dia., bears S.44°W., 40½ lks. dist., with scribe marks ¼ S3 BT 1543 visible on partially healed blaze.

(Cont. Next Page)

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

At the corner point
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in
the ground, directly over iron pipe, with brass cap marked

T 33 S R 7 W

^{1/4}
S 3 | S 2
1975

Fd. OK, DCSO, G. Langlitz, Sept. 23, 1976, C.S. File 59/24
FD. OK by Lloyd Smith, 3/85, M 98-47
Fd. OK by B. Shaner - March 1996 - M 124-10