

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 9036)

Set a Fir post, 40" long, 20" in the ground, mkd. ¼ S on N. side, for the ¼ sec. corner, from which
A Fir 24" dia., bears S.8°W., 66 lks. dist., mkd. ¼ S BT
A Pine 14" dia., bears N.10°W., 97 lks. dist., mkd. ¼ S BT

Not FD by DCSO JP, 4/1968 (added 10/18/2016) C.S. 54/36-171
Could not find any evidence of 24" fir or 14" pine. Fd E-W blazed line, one fir remaining in cut units possible BT, it stand approx. right dist. form the line but no evidence of scar or bark scribing. Area also burnt years ago.

Survey by Richard L. Templin, Jr. - For: C & D Lumber Co. - July 11, 1977 - C.S. File 58/93

Set 1½" Iron pipe (per survey by Templin, filed with the Josephine Co. Surveyors Office as CS 148-77)
BTs - A S.Pine 45" bears N.15°W., (Rec. N.10°W., 64.02 ft. (O.B.T.)
A D.Fir 15" bears N.60°E., 3.0 ft.