

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 540700

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. Section 2 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by C. E. Masters - For: Corwin - March 29, 1971 -
M 41-39

Set 5/8" Iron rod and scribed:
10" Madrone S.55°W., 26.90 ft.
8" Madrone S.11°E., 16.10 ft.
Found 1" I.P. N.9°33'W., 17.28 ft.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud,
Cadastral Surveyors, Under Group #845, surveyed April/Nov.
1975 (DCSO records Vol. 41 Page(s) 16267)

(At 28.94 chs. N.89°00'W of S C Secs. 35 and 36, T32-7)

**From this point, a point established and recorded by Claude
Masters, L.S. #457, in 1971, bears South, 0.08 chs. dist.,
monumented with an iron rod, 5/8" dia., firmly set,
projecting 3" above ground, from which**
A Madrone 8" dia., bears S.8°E., 24½ lks. dist., with
scribe marks ¼ S2 RS 457 BT visible on partially healed
double blaze.
A Madrone 10" dia., bears S.64°W., 40 lks. dist., with
scribe marks ¼ S2 RS 457 BT visible on partially healed
blaze.

FD. OK - R. Mason - Oct. 2, 1997 - M127-64 & CS 65/16-3
Found ok by K.DeGroot - 4/1998 - M128-50

James McIntosh - For: State of Oregon, Dept. of Forestry -
June 2001 - M 138-51

Condition report
Found - 5/8" IR, (1971) in place.
10" Madrone S.55°W. 26.90' (now 13" S.68°W., scribes
visible)
8" Madrone S.11°E., 16.10' (now 9" S.02°E., scribes
visible)
1" IP N.09°33'W., 17.28' (in place)