

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 9031)

-----  
Set Laurel post 4 ft. long, 4" sq., 2 ft. in the ground for corner to secs. 1, 2, 11 and 12, marked T33S R7W S1 on NE.; S12 on SE.; S11 on SW.; and S2 on NW. faces, with 5 notches on S. and 1 notch on E. edges, from which  
A Fir 14" dia., bears N.35°E., 78 lks. dist., mkd. T33S R7W S1 BT.  
A Fir 26" dia., bears S.86°E., 24 lks. dist., mkd. T33S R7W S12 BT.  
A Fir 14" dia., bears S.78°W., 38 lks. dist., mkd. T33S R7W S11 BT.  
A Fir 14" dia., bears N.76°W., 34 lks. dist., mkd. T33S R7W S2 BT.

Survey by Marvin Ramsey - For: J.H. Baxter Co. - Feb. 4-12, 1965 - C.S. File 51/310

-----  
Determined from the original BTs:  
16" D.Fir snag, bears N.37½°E., 78 lks. dist. with axe face, marks burned out.  
36" D.Fir bears S.86°E., 24 lks., with partial scribe marks on the bark.  
D.Fir remains of a burned out stump bears S.75°W., 38 lks. dist.  
18" D.Fir snag, bears N.78°W., 34 lks. with mkd. T33SR7 on the bark.  
Set 1" I.Pipe 3 ft. long, 2" dia., 28" in the ground, from which, new BTs:  
34" D.Fir bears N.61½°E., 87 lks. mkd. T33S R7W S11 RS404 BT.  
28" D.Fir bears S.59°W., 41 lks. mkd. T33S R7W S11 RS404 BT.  
26" D.Fir bears N.82°W., 185 lks. mkd. T33S R7W S2 RS404 BT.

BLM resurvey by John Jelley, Rollin Aanrud, and Lynn Roseberry, Cadastral Surveyors, under Group #'s 350 and 688, surveyed May 1969/March 1970 (DCSO records Vol. 35 Page(s) 14479)

-----  
The original sec. cor., perpetuated and recorded by Ramsey in 1965, with an iron pipe 2" dia., firmly set, projecting 8" above ground, from which the original bearing trees:  
(Cont. Next Page)

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A sawed Fir stump 16" dia., bears N.35°E., 73 lks. dist., with no marks visible. (Rec. 78 lks.)

A Fir 36" dia., bears S.86°E., 24 lks. dist., with illegible scribe marks visible on bark blaze.

The root crown of a Fir, size indeterminate, bears S.78°W., 38 lks. dist.

A root hole bears N.76°W., 34 lks. dist., with a down Fir 18" dia., alongside, with scribe marks T33S R7 visible on bark blaze.

and bearing trees mkd. by Ramsey

A sawed Fir stump 34" dia., bears N.59°E., 87 lks. dist., with scribe marks T33S R7W S1 RS 404 BT visible on open blaze.

A Fir 28" dia., bears S.57°W., 41 lks. dist., with healed blaze.

A Fir 26" dia., bears N.84°W., 185 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 33 S R 7 W  
S 2 S 1  
S 11 S 12  
1969

Reset iron pipe alongside iron post.