TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 600620

PRIMARY CORNER DESCRIPTION So. 1/16 Cor. for Secs. 1 and 2

Alias Description
Alias Description
Alias Description
Alias Description

Survey by Marvin C. Ramsey - For: J.H. Baxter & Co. - Feb. 4-12, 1965 - C.S. File 51/310

At proportionate distance
Set I.Pipe, 3 ft. long, 1" dia., 28" in ground, mkd. RS404, from which
- 22" D.Fir bears S.17°E., 217 lks. dist., mkd. S 1/16 S1 RS404 BT.
- 12" Madrona bears S.60°W., 72 lks. mkd. S 1/16 S2 RS404 BT.

BLM resurvey by John Jelley, Rollin Aanrud, and Lynn Roseberry, Cadastral Surveyors, under Group #'s 350 and 688, surveyed May 1969/March 1970 (DCSO records Vol. 35 Page(s) 14480)

The S 1/16 sec. cor. of secs. 1 and 2, established and recorded by Ramsey in 1965, monumented with an iron pipe 1½" dia., firmly set, extending 8" above the ground, with bronze washer in top, mkd. RS 404, from which bearing tree mkd. by Ramsey
- A Fir 19" dia., bears S.17°E., 217 lks. dist., with healed blaze.
- A Madrone 11" dia., bears S.60°W., 72 lks. dist., with scribe marks S 1/16 S2 RS 404 BT visible on bark.

At the corner point
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked
S 1/16
S 2 S 1
1969
from which a new bearing tree
- A Madrone 6" dia., bears N.65°W., 33 lks. dist., mkd. S 1/16 S2 BT.

Insert iron pipe inside iron post.