

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 9032-33)

Set a Pine post, 3 ft. long, 3" sq., 20" in the ground mkd. 1/4 S on W. side for the 1/4 sec. corner. Made stone mound about same. No witness trees near and pits impracticable.

Survey by Marvin C. Ramsey - For: J.H. Baxter & Co. - Feb. 4-12, 1965 - C.S. File 51/310

Point for the 1/4 cor. at proportionate distance; fail to find any evidence of the original corner after careful search. Set I.Pipe 3 ft. long, 1 1/2" dia., 28" in ground, mkd. RS404, from which
10" D.Fir bears S.10 1/2°E., 112 lks. dist., mkd. 1/4 S1 RS404 BT.
8" Madrona bears N.79°W., 34 lks. dist., mkd. 1/4 S2 RS404 BT.

BLM resurvey by John Jelley, Rollin Aanrud, and Lynn Roseberry, Cadastral Surveyors, under Group #'s 350 and 688, surveyed May 1969/March 1970 (DCSO records Vol. 35 Page(s) 14480-81)

The 1/4 sec. cor., reestablished and recorded by Ramsey, in 1965, by proportionate methods; there is no remaining evidence of the original corner. The corner point is monumented with an iron pipe, 1 1/2" dia., firmly set, projecting 6" above ground, with bronze washer in top mkd. RS404, from which bearing trees mkd. by Ramsey:

A Fir 11" dia., bears S.12°E., 112 lks. dist., with healed blaze.

A Madrone 7" dia., bears N.84°W., 34 lks. dist., with scribe marks 1/4 S2 RS 404 BT visible on bark.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 33 S R 7 W

1/4
S 2 S 1
1969

from which a new bearing tree

A Chinquapin 11" dia., bears S.67 1/4°W., 31 lks. dist., mkd. 1/4 S2 BT.

Insert iron pipe inside iron post.

continued next page

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

James McIntosh - For: State of Oregon, Dept. of Forestry -
June 2001 - M 138-51

Found - BLM brass cap, 1969 (in place)
10" Fir (1965) S.10½°E., 112 lks (now 25" in place,
face closed)
8" Madrone (1965) N.79°W., 34 lks. (now 10", 23.9'
face closed)
11" Chinquapin (1969) S.67¼°W., 31 lks., (now 16" in
place, face closed)

Rewitnessed -
WP (Orange carsonite marker CBM-250 labeled witness
post) N.30°W., 3.60' to base.
WP (Orange carsonite marker CBM-250 labeled witness
post) S.40°E., 2.95' to base.