

PRIMARY CORNER DESCRIPTION N. Sec. cor. for 1 and 2 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 9033)

(At 10.41 chs. East of corner to secs. 35 and 36, T32-7)
Set a Fir post, 4 ft. long, 4" sq., 24" in the ground for closing corner to secs. 1 and 2, marked C C T33S R7W on S.; S1 on E.; S2 on W.; faces, also 1 notch on E. and 5 notches on W. faces, from which
A Cedar 36" dia., bears S.35°E., 20 lks. dist. mkd. T33S R7W S1 BT.
A Fir 32" dia., bears S.44°W., 28 lks. dist., mkd. T33S R7W S2 BT.
A Fir 56" dia., bears N.65°W., 21 lks. dist., mkd. T32S R7W S36 BT.

Survey by Marvin C. Ramsey - For: J.H. Baxter & Co. - Feb. 4-12, 1965 - C.S. File 51/310

Found - Orig. BT, 36" Cedar sawed stump, bears S.32°E., 20 lks., with axe marks, scribe marks burned out.
Orig. BT, 32" D.Fir sawed stump, bears S.45°W., 28 lks. with a partial scribe mark exposed.
Orig. BT, 56" D.Fir snag bears N.60°W., 21 lks. with axe face, marks obliterated from decay.
Set Iron pipe 3 ft. long, 2" dia., 28" in the ground mkd. RS404, from which an unmarked I.Pipe, 1" dia., 6" above ground bears S.53°E., 6 lks.
New BTs -10" D.Fir bears S.57°E., 36 lks. mkd. T33S R7W S1 RS404 BT.
16" D.Fir bears S.10°W., 10 lks. mkd. T33S R7W S2 RS404 BT.

Douglas Co. Surveyors Office, John Powell and Frank Jones - Dec. 5, 1967 - C.S. File 54/36-100

Found - 2" I.Pipe with 4" flange at sec. cor.
1" I.Pipe, S.53°E., 4.0 ft.
10" D.Fir now stob, S.57°E., 23.8 ft. shows pitched over scribing.
16" D.Fir S.10°W., 6.6 ft. shows pitched over scribing.
New BT - 12" D.Fir S.82°E., 22.3 ft. mkd. T33S R7W S1 CC CS BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION N. sec. cor. for 1 and 2 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by John Jelley, Rollin Aanrud, and Lynn Roseberry, Cadastral Surveyors, under Group #'s 350 and 688, surveyed May 1969/March 1970 (DCSO records Vol. 35 Page(s) 14470)

The original closing corner, perpetuated and recorded by Ramsey in 1965, with an iron pipe 2" dia., firmly set, extending 8" above ground, with bronze washer in top mkd. RS 404, from which the original bearing trees:

A sawed Cedar stump 36" dia., bears S.35°E., 20 lks. dist., with no marks visible.

A sawed Fir stump 28" dia., bears S.44°W., 28 lks. dist., with no marks visible.

The rotted remains of a Fir stump, size indeterminate, bears N.60°W., 24 lks. dist., with no marks visible. (Rec. N.65°W., 21 lks.)

and bearing trees mkd. by Ramsey

A Fir snag 10" dia. bears S.57°E. 36 lks. with open blaze.

A Fir 15" dia., bears S.10°W., 10 lks. with healed blaze.

and a bearing tree mkd. by Powell in 1967

A Fir 15" dia., bears S.82°E., 33 lks., with open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 32	S	R	7	W
	S	36		
	S	2	S	1
T 33	S	R	7	W
	C	C		
				1969

Reset iron pipe alongside iron post.

From this point an iron pipe 1" dia., firmly set, projecting 6" above ground, of which I have no record, bears S.61½°E., 0.06 chs. dist.

James McIntosh - For: State of Oregon, Dept. of Forestry - June 2001 - M 138-51

Found - BLM brass cap, 1969 with 1965 2" pipe with bronze washer alongside (in place)

36" Cedar (1881) S.35°E., 20 lks. (now 31"x3' high stump in place, no marks visible.)

32" Fir (1881) S.44°W., 28 lks. (now 25"x2' high rotted stump in place, no marks visible)

56" Fir (1881) N.65°W., 21 lks. (now 10"x8' high rotted stob in place, no marks visible.)

10" Fir (1965) S.57°E., 36 lks., (now 10"x4' high rotted stob in place, axe work visible)

continued next page

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION N. Sec. cor. for 1 and 2 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

16" Fir (1965) S.10°W., 10 lks (now 22" in place, face closed BT tag.)
1" IP S.53°E., 6 lks., (in place)
12" Fir (1967) S.82°E., 22.3' (now 25" in place, face closed) added BT tag.

Rewitnessed -
WP (Orange carsonite marker CBM-250 labeled witness post) S.40°E., 3.9' to base.
WP (Orange carsonite marker CBM-250 labeled witness post) S.50°W., 3.1' to base.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 4/23/25 - C.S. File 67/60-21

Found - 3¼" BLM brass cap up 1". 2" iron pipe on N.N.E. edge up 4".
31"x3' high cedar stump S.35°E. 13.2 ft (Rec 20 lks)
Very rotted 25"x1 ft fir stump S.44°W. 13.9 ft (Rec 28 lks)
28" D. Fir S.10°W. 6.6 ft (Rec 10 lks) healed blaze
Add 3½" mag nail right side center.
32" D. Fir S.82°E. 22.3 ft healed blaze. Add 3½" mag nail left side center.
2 - carsonite posts labeled witness post:
S.40°E. 3.9 to base.
S.50°W. 3.1 to base.

Notes - Mon. is approx. 50 ft north of paved road.
Mon. on flat ground on a wooded flood plain.
Compass decl. 14½°E.
Leica Lat & Long
Lat - 42°44'22.05746 N. Long - 123°29'04.01544 W.