

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

NOT IN DOUGLAS COUNTY

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #420, dated Sept. 16, 1881 (DCSO records Vol. 21 Page(s) 9028)

Set a fir post, 3' long, 3" sq., 16" in the ground, for ¼ sec. cor. mkd. ¼ S on N. face, from which
A Live Oak, 7" dia., bears N.35°W., 7 lks., mkd ¼ S BT.
A Live Oak, 15" dia., bears S.55°E., 20 lks. mkd ¼ S BT.

BLM resurvey by John Jelley, Rollin D. Aanrud, and Lynn Roseberry, Cadastral Surveyors, Under Group #'s 350 & 688, surveyed May 1969/March 1970 (DCSO records Vol. 35 Page(s) 14474-5)

The ¼ sec. cor. of secs. 13 & 24, established by Richard L. Templin, Jr. R.E. #3024, in 1955, monumented with an iron pipe, 3/4" dia., firmly set, projecting 6" above ground, from which:

A fir, 35" dia., bears N.9°E., 45½ lks., w/healed blaze.
A fir, 18" dia., bears S.15°E., 41 lks., w/pitched over blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T33S R7W
 S 13
¼ S 24
 1969

Deposit iron pipe inside the iron post.