

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 9032)

Set a Laurel post, 3 ft. long, 3" sq., 20" in the ground, mkd. $\frac{1}{4}$ S on N. side for the $\frac{1}{4}$ sec. corner, from which
A Fir 28" dia., bears N.47°E., 23 lks. dist. mkd. $\frac{1}{4}$ S BT.
A Fir 22" dia., bears S.18°E., 23 lks. dist. mkd. $\frac{1}{4}$ S BT.

Not Fd. by DCSO JP 3/4/1968 (added 10/18/2016) area logged and burnt - C.S. file 54/36-169

BLM resurvey by John Jelley, Rollin Aanrud, and Lynn Roseberry, Cadastral Surveyors, under Group #'s 350 and 688, surveyed May 1969/March 1970 (DCSO records Vol. 35 Page(s) 14478)

Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked
T 33 S R 7 W
 $\frac{1}{4}$ $\frac{S 1}{S 12}$
1969

from which
A Pine 4" dia., bears N.13°E., 39 lks. dist., mkd. X BT.
A Madrone 5" dia., bears S.66°W., 32 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S12 BT.