

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 640640

PRIMARY CORNER DESCRIPTION Center 1/4 Corner for Section 1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM survey by John Jelley, Rollin Aanrud, and Lynn Roseberry, Cadastral Surveyors, under Group #'s 350 and 688, surveyed May 1969/March 1970 (DCSO records Vol. 35 Page(s) 14482-83)

Point for the center ¼ sec. cor. of sec. 1, at intersection with the E. and W. center line.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked T 33 S R 7 W

C ¼ S 1
1969

from which

A Fir 41" dia., bears N.74½°E., 70 lks., mkd. C¼ S1 BT.

A Fir 15" dia., bears S.72°W., 76 lks., mkd. C¼ S1 BT.

James McIntosh - For: State of Oregon, Dept. of Forestry - June 2001 - M 138-51

Found - 5/8" IR, 1971 (in place)

6" Madrone N.36°W., 2.90' (now 9" in place, face closed BT tag.)

4" Madrone N.67°W., 34.84' (now 11" in place, face closed)

4" Madrone S.42°45'E., 73.25' (now 8" in place, face closed BT tag.)

Power pole S.26°15'W., 77.92' (in place.)

Rewitnessed -

WP (Orange carsonite marker CBM-250 labeled witness post) S.69°E., 3.2' to base.

WP (Orange carsonite marker CBM-250 labeled witness post) S.74°W., 3.1' to base.