

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 640700

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. Sec. 1 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by D.J. Theno - Sept. 6, 1950 - C.S. File 40/274

At corner, set 2" Iron pipe by proportional measurement, from which

- 11" Fir N.37°E., 1.0 ft.
- 12" Fir S.69°E., 27.8 ft.

Fd. OK, DCSO, John Powell, Dec. 5, 1967, C.S. File 54/36-101

BLM resurvey by John Jelley, Rollin Aanrud, and Lynn Roseberry, Cadastral Surveyors, under Group #'s 350 and 688, surveyed May 1969/March 1970 (DCSO records Vol. 35 Page(s) 14469)

The ¼ sec. cor. of sec. 1 only, established and recorded by Douglas Theno in 1950, at midpoint on the N. bdy. of sec. 1, monumented with an iron pipe 2" dia., firmly set, projecting 12" above ground, from which bearing trees mkd. by Theno:

- A Fir 15" dia., bears N.37°E., 2 lks. dist., with scribe marks ¼ S visible on opened blaze.
- A Fir 17" dia., bears S.69°E., 42 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

¼ S 1
T 33 S R 7 W
1969

from which a new bearing tree

- A Live Oak 6" dia., bears S.72½°W., 46 lks. dist., mkd. ¼ S1 BT.

Reset iron pipe alongside iron post.

Found OK by R. Wytcherley, Feb. 2001 - M136-55

Found OK by R. Wytcherley, May 2006 - M150-70

Fd. BC & BTs by R. Wytcherly, 4/2008 - M156-10