

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13 & 24; 18 & 19 T33-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

NOT IN DOUGLAS COUNTY - See Josephine County for more info

GLO survey by Wells Lake and Geo. Hyde, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 21 Page(s) 9002-3)

-----  
Set post cor. to secs. 13, 18, 19, & 24 on S slope from which:

- A Yellow Pine, 15" dia., bears N.83°W., 20 lks.
- A B.Oak, 10" dia., bears S.74°E., 75 lks.
- A Live Oak, 8" dia., bears S.10°W., 3 lks.
- A Fir, 20" dia., bears N.52°E., 19 lks.

Cor. fd and used - GLO survey by W.H. Byars, Deputy Surveyor, under Contract #420, dated Sept. 16, 1881 (DCSO records Vol. 21 Page(s) 9027-8)

BLM remonumentation survey by Joseph S. Gawron under Group #350, dated May 3, 1957. (DCSO records Vol. 33 Page(s) 13855))

-----  
The cor. of secs. 13, 18, 19, & 24, on the W. bdy of the Tp., determined from the three original BTs:

- A D.Fir, 50" dia., bears N.52°E., 19 lks., mkd: T33S R6W S18 on opened blaze.
- A B.Oak, 24" dia., bears S.74°E., 75 lks., w/rotted blaze, no marks remaining.
- A Live Oak stool, bears S.10°W., 3 lks.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T 33 S  
R 7 W R 6 W  
S 13 S 18  
S 24 S 19  
1963

from which

- A forked B.Oak, 36" dia, bears N.26°E., 111 lks., mkd: T33S R6W S18 BT.
- A D.Fir, 6" dia, bears S.41°E., 106 lks., mkd: T33S R6W S19 BT.
- A B.Oak, 6" dia, bears S.18°W., 48 lks., mkd: T33S R7W S24 BT.
- A Madrone, 6" dia, bears N.20°W., 46½ lks., mkd: T33S R7W S13 BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Cor. Secs. 13 & 24; 18 & 19 T33-6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Fd & used in BLM resurvey by John Jelley, Rollin D. Aanrud, and Lynn Roseberry, Cadastral Surveyors, Under Group #'s 350 & 688, surveyed May 1969/March 1970 (DCSO records Vol. 35 Page(s) 14471).

James M. McIntosh - For: State of Oregon - Dept. of Forestry  
- Feb. 2001 - M 136-74

- 
- Found - BLM 2½"x28" iron pipe w/brass cap, 1963 (in place)  
20" Fir (1855) N.52°E., 19 lks., (now 54" in place, face exposed no scribes visible, BT Tag)  
10" B.Oak (1855) S.74°E., 75 lks. (now 31" in place, top face open & rotted bottom face closed BT tag)  
36" B.Oak (1963) N.26°E., 111 lks. (now 41" double trunked in place, face closed, BT tag)  
6" Fir (1963) S.41°E., 106 lks. (now 18" in place, face closed, BT tag)  
6" B.Oak (1963) S.18°W., 48 lks. (now 10"x2' high stump in place, no marks visible, remaining portion of tree lying downhill w/BT tag attached)  
6" Madrone (1963) N.20°W., 46½ lks (now 10" in place, face closed BT tag)  
27" Fir S.38°W., 6.4' to closed face, axe work visible, no record.
- New - Orange carsonite marker CBM-250 labeled witness post N.50°W., 3.80' to base.  
Orange carsonite marker CBM-250 labeled witness post S.27°W., 2.70' to base.