

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 13; and 18 of T33-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wells Lake and Geo. W. Hyde, Deputy Surveyors,
under Contract #54, dated Feb. 19, 1855 (DCSO records Vol.
21 Page(s) 9002)

Set quarter sec. post on NE. side of mountain, from which
A Fir 24" dia., bears N.52°W., 26 lks.
A Fir 16" dia., bears N.80°E., 24 lks.

BLM dependent resurvey by Joseph S. Gawron under Group #'s
350 and 526 surveyed Sept. 1963/July 1964 (DCSO records Vol.
33 Page(s) 13836-37)

The ¼ sec. cor., determined from the original bearing trees:
A D.Fir dead and down, 22" dia., bears N.80°E., 24 lks.
dist., mkd. ¼ S BT on opened blaze.
A D.Fir 40" dia., bears N.52°W., 32 lks. dist., mkd. ¼ S
on opened blaze. (Rec. 26 lks.)

At the corner point

Set an iron post, 30" long, 2½" dia., 18" in the ground, to
solid rock, and in a mound of stone, 3 ft. base, to top, with
brass cap mkd:

¼
S 13 | S 18
R 7 W | R 6 W
T 33 S
1963

from which

A D.Fir 6" dia., bears S.72°E., 140 lks., mkd. ¼ S18 BT.
A D.Fir 10" dia., bears S.78°W., 74 lks., mkd. ¼ S13 BT.

Cor. used in BLM survey by Roseberry, Aanrudd & Jelley, Group
#350, surveyed 1969/70 (DCSO records, Vol. 35 Pg 14471)

James M. McIntosh - For: State of Oregon - Dept. of Forestry
- Feb. 2001 - M 136-74

Found - BLM 2½"x28" iron pipe w/brass cap, 1963 (in place)
24" Fir (1855) N.52°W., 32 lks (now 40" in place,
face exposed partial scribes visible, BT tag.
6" Fir (1963) S.72°E., 140 lks. (now 12" in place,
face closed)
10" Fir (1963) S.78°W., 74 lks. (now 11"x25' high
snag in place, face open partial scribed visible.
New - Orange carsonite marker CBM-250 labeled witness post
N.69°W., 2.9' to base.
Orange carsonite marker CBM-250 labeled witness post
S.53°E., 3.1' to base.

Fd. BC & 3 BTs, by Kris DeGroot - 11/2014 - M166-21