

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 12; and S. 7, T33-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wells Lake and Geo. W. Hyde, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 21 Page(s) 9001)

Set quarter sec. post on steep NW descent, from which
A Fir 24" dia., bears N.32°W., 41 lks.
A Fir 36" dia., bears N.35°E., 19 lks.

BLM dependent resurvey by Joseph S. Gawron under Group #'s 350 and 526 surveyed Sept. 1963/July 1964 (DCSO records Vol. 33 Page(s) 13838)

The ¼ sec. cor., determined from the remains of the original bearing trees:

A D.Fir snag, 40" dia., bears N.45°E., 19 lks. dist., mkd.
¼ S BT on opened blaze. (Rec. N.35°E.)
A D.Fir snag, 30" dia., bears N.32°W., 41 lks. dist., mkd.
¼ S BT on opened blaze.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap marked ¼

S 12 S 7
R 7 W R 6 W
T 33 S
1963

from which

A D.Fir snag 36" dia., bears N.52°E., 33 lks. dist., mkd.
¼ S7 BT.
A D.Fir snag 40" dia., bears S.14°W., 130 lks. dist., mkd.
¼ S12 BT.

There are no suitable live bearing trees available within limits.