

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7 of T33-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wells Lake and Geo. W. Hyde, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 21 Page(s) 9001)

Set post cor. to secs. 1, 6, 7 and 12 on S. slope, from which
A Laurel 4" dia., bears N.25°E., 45 lks.
A Laurel 4" dia., bears N.47°W., 29 lks.
A Laurel 3" dia., bears S.79°W., 30 lks.
A Laurel 4" dia., bears S.49°E., 55 lks.

Cor. fd. and used in GLO survey by Byars, 1882 - (DCSO records, Vol. 21 Page 9022 and Page 9032)

BLM dependent resurvey by Joseph S. Gawron under Group #'s 350 and 526 surveyed Sept. 1963/July 1964 (DCSO records Vol. 33 Page(s) 13839)

Point for the cor. at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 30 ins. long, 2 1/2 ins. dia., 26 ins. in the ground, with brass cap marked
T 33 S
R 7 W R 6 W
S 1 S 6
S 12 S 7
1963

from which
A D.Fir 30" dia., bears S.27°E., 118 lks. dist., mkd. T33S R6W S7 BT.
A Ponderosa Pine 25" dia., bears S.53°W., 29 lks. dist., mkd. T33S R7W S12 BT.
A Ponderosa Pine 30" dia., bears N.65°W., 122 lks. dist., mkd. T33S R7W S1 BT.
No suitable bearing trees available within limits in Sec. 6.

Corner used in BLM survey by Jelley, Aanrud and Roseberry, Group #'s 350 and 688, surveyed May 1969/March 1970 (DCSO records, Vol. 35 Page 14472)