

TOWNSHIP 33 RANGE 07 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; and 6 of T33-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wells Lake and Geo. W. Hyde, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 21 Page(s) 9001)

Set quarter sec. post on steep N. descent, from which
A Chinquapin 10" dia., bears N.14°W., 60 lks.
A Cedar 12" dia., bears S.40°E., 22 lks.

BLM dependent resurvey by Joseph S. Gawron under Group #'s 350 and 526 surveyed Sept. 1963/July 1964 (DCSO records Vol. 33 Page(s) 13840)

Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. dia., 26 ins. in the ground, with brass cap marked ¼

S 1 S 6
R 7 W R 6 W
T 33 S
1963

from which

A D.Fir 14" dia., bears N.17°E., 13½ lks. dist., mkd. ¼ S6 BT.

An I.Cedar 6" dia., bears N.10°W., 42 lks. dist., mkd. ¼ S1 BT.

Fd. and used in BLM survey by Jolley, Aanrud and Roseberry, Group #'s 350 and 688, Survey, May 1969/March 1970 (DCSO records, Vol. 35 Pg. 14472)

Cor. Fd. OK, by G. Nygren, March 1994, M 118-79