

16022

Dependent Resurvey of a Portion of the North Boundary
of Donation Land Claim No. 39,
T. 22 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 22 S R 7 W S 20 C 39 1977 from which new bearing trees A fir, 5 ins. diam., bears S. 30½° E., 99 lks. dist., mkd. X BT. A fir, 20 ins. diam., bears S. 15° W., 101 lks. dist., mkd. T22S R7W C39 BT. Corner is located at intersection of wire fences, fences extend S. and W. N. 88° 56' W., along the N. bdy. of Claim No. 39. Descend 560 ft. over SW. slope, through open pasture lands.
6.80	Corner of wire fences, extending N. and E.
34.50	Gravelled road, 35 lks. wide, bears N. 20° W. and S. 20° E.
39.50	Elk Creek, 100 lks. wide, course S. 25° E.; asc. 350 ft. over E. slope.
46.64	Intersect the line bet. secs. 19 and 20.
	Point for the crossing closing cor. of secs. 19 and 20, hereinbefore described. From this point, the ¼ sec. cor. of secs. 19 and 20, bears S. 0° 15' E., 8.97 chs. dist., hereinbefore described. Ascend 90 ft. over E. slope.
50.75	Top of ascent, slopes S. 40° E.; desc. 30 ft. over SW. slope.
56.53	The SE. cor. of Claim No. 41, on the N. bdy. of Claim No. 39, perpetuated and recorded by J. W. Cole, Deputy County Surveyor, in 1915, when original evidence was still in existence, and further perpetuated by A. R. Evans, Deputy County Surveyor, in 1950, monumented with an iron rod, 1 in. diam., firmly set, projecting 1 in. above ground, from which a bearing tree mkd. by Evans: An oak, 32 ins. diam., bears N. 20½° W., 452 lks. dist., with healed blaze. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron rod, with brass cap mkd. T 22 S R 7 W S 19 C 41 C 39 1977