

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A sawed fir stump, 27 ins. diam., bears S. 27° E., 61 lks. dist., with healed blaze.

A fir, 36 ins. diam., bears S. 3¼° W., 46 lks. dist., with healed blaze.

A sawed fir stump, 39 ins. diam., bears N. 12¼° W., 176 lks. dist., with healed double blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.

T 22 S	R 7 W
S 20	S 21
S 29	S 28
1996	

from which new bearing trees

A fir, 15 ins. diam., bears N. 85 3/4° E., 196 lks. dist., mkd. T22S R7W S21 BT.

A fir, 8 ins. diam., bears S. 78 3/4° E., 196 lks. dist., mkd. T22S R7W S28 BT.

A fir, 22 ins. diam., bears N. 16 3/4° W., 98 lks. dist., mkd. T22S R7W S20 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Buried 2½ in. diam. iron pipe alongside stainless steel post and drove a metal fence post S., 0.02 chs. dist. from the corner.

Dependent Resurvey of a Portion of Donation Land Claim No. 45,
T. 22 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the survey by Josiah A. Burnett
and Dennis Hathorn, in 1856-57)

From the SW. cor. of Donation Land Claim No. 45, reported to have been perpetuated by M.B. Germond, further perpetuated by Floyd J. Cole, Deputy County Surveyor, in 1914, from original evidence no longer in existence, recorded in the Douglas County Surveyor's Office, Field Book 39, page 5; monumented with a stone, 12 x 16 x 24 ins., firmly set, projecting 8 ins. above ground:

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.