

Dependent Resurvey of a Portion of Donation Land Claim No. 45,
T. 22 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C 45 ----- S 28 1996</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 86 3/4° E., 24 lks. dist., mkd. S28 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 62¼° W., 13 lks. dist., mkd. C45 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0° 15' 09" E., on the most westerly E. bdy. of Donation Land Claim No. 45.</p> <p>Descend over broken NE. slope, changing to NW. slope, through moderate timber and undergrowth.</p>
6.329	<p>Intersect the section line bet. secs. 21 and 28. Point for the crossing closing cor. on the sec. line bet. secs. 21 and 28 and the most westerly E. bdy. of Donation Land Claim No. 45, hereinbefore described.</p> <p>Descend over NW. slope.</p>
25.60	<p>Creek, 10 lks. wide, course N. 50° E.; asc. over SE. slope.</p>
48.35	<p>Ridge, bears N. 30° W. and S. 30° E.; desc. over NE. slope.</p>
56.30	<p>Oregon State Highway No. 38, asphalt surfaced, 60 lks. wide, bears N. 75° E. and S. 65° W.</p>
68.60	<p>Elk Creek, 125 lks. wide, course S. 85° W.; asc. over S. slope.</p>
69.576	<p>Point for the interior "L" corner of Donation Land Claim No. 45, at proportionate distance, determined by the Grant Boundary Method between the original SW. cor. of Donation Land Claim No. 45 and the restored NE. cor. of Donation Land Claim No. 45, there is no remaining evidence of the original corner; no permanent monument set.</p> <hr/> <p>S. 89° 40' 51" E., on the most northerly S. bdy. of Donation Land Claim No. 45.</p> <p>Over nearly level ground, through moderate timber, dense undergrowth and open pastures.</p>
27.60	<p>Oregon State Highway No. 38, asphalt surfaced, 50 lks. wide, bears N. 40° E. and S. 40° W.</p>