

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Bdrs., Claim No. 43, T. 22 S., R. 7 W.

CHAINS

15.01

The interior cor. on the E. bdy. of Claim No. 43, determined at record bearing and distance from the original bearing trees:

A white oak, 20 ins. diam., bears N. 4° E., 910 lks. dist., with scribe marks BT visible on opened blaze.

A stump hole and oak roots, bears N. 0½° W., 885 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked

T 22 S R 7 W

C 43 | S 18
1968

from which

A fir, 18 ins. diam., bears N. 29° E., 540 lks. dist., mkd. T22S R7W S7 BT.

A fir, 25 ins. diam., bears S. 19½° W., 445 lks. dist., mkd. T22S R7W C43 BT.

Set a 6 ft. steel fence post alongside the iron post.

Dependent Resurvey of the Boundaries of Donation Land Claim No. 44, T. 22 S., R. 7 W., and Donation Land Claim No. 40, T. 22 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the 1856 survey by Dennis Hathorn)

From the NE. cor. of Donation Land Claim No. 44 in sec. 7, T. 22 S. R. 7 W., perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1929, monumented with a sandstone, 12 x 6 x 6 ins., marked CS on NE. face, now alongside an iron post, 1½ ins. diam., firmly set, projecting 8 ins. above ground, by Milo E. Godfrey, Deputy County Surveyor, in 1962, with brass cap marked

COUNTY SURVEYORS OFFICE

T 22 S
R 7 W
DLC | N
44 | E
1962

from which the original bearing trees:

A rotted fir stump, 38 ins. diam., bears N. 14½° E., 728 lks. dist., with scribe marks BT visible on opened blaze.

A rotted fir stump, 30 ins. diam., bears N. 3½° W., 556 lks. dist., with scribe marks BT visible on opened blaze.

and trees marked by Godfrey in 1962: