Resurvey of Boundaries, Claim No. 49, T. 22 S., R. 8 W.

CHAINS	
63.41	The cor. of Claim No. 49, on the left bank of the Umpqua River, perpetuated with an iron pipe, 2 ins. diam., 10 ins. above ground, firmly set. This point has long been locally accepted as the corner position, and is now adopted as the best available evidence of the original corner. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked T 22 S R 8 W S 4 C 49 1963 from which A fir, 12 ins. diam., bears S. 18° W., 48 lks. dist., mkd. T22S R8W C49 BT. No other suitable bearing tree available. Reset the iron pipe alongside the iron post.

Dependent Resurvey of the Boundaries of Claim No. 54, T. 22 S., R. 8 W., Willamette Meridian, Oregon (Restoring the 1856 survey by Dennis Hathorn.)

	Beginning at the NW. cor. of Claim No. 54 in sec. 28, which is perpetuated by the cor. of old barbed and woven wire fences extending north, east, and south. This point has long been accepted by local property owners as the true point for the NW. cor. of Claim No. 54. It is now adopted as the best available evidence of the corner position. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked T 22 S R 8 W S 28 C 54 1964 from which A fir, 23 ins. diam., bears N. 9¼° W., 218 lks. dist., mkd. T22S R8W S28 BT. A fir, 6 ins. diam., bears S. 10½° W., 197 lks. dist., mkd. T22S R8W S28 BT. S. 89° 58' E., on a blank line along the N. bdy. of Claim No. 54.
22.53	Point for closing cor. at intersection with the line bet. secs. 27 and 28. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked