

County Surveyor's Record, Douglas County, Oregon

14904

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

A fir, 20 ins. diam., bears N. 86 1/2° W., 53 lks. dist., with healed blaze.

A fir, 15 ins. diam., bears N. 37° W., 161 lks. dist., with healed blaze.

and new bearing trees

A white fir, 8 ins. diam., bears S. 51° E., 19 1/2 lks. dist., mkd. T22S R9W S16 BT.

A fir, 5 ins. diam., bears S. 5 3/4° W., 25 lks. dist., mkd. T22S R9W S17 BT.

From the same point, the SE. cor. of Donation Land Claim No. 38, bears S. 74° 17' E., 17.71 chs. distant, determined at record distance from the original bearing trees:

A fir snag, 33 ins. diam., bears S. 27 1/2° E., 25 lks. dist., with scribe marks BT visible on opened blaze. (Record, S. 20° E.)

A fir, 34 ins. diam., bears N. 87 1/2° W., 100 lks. dist., with scribe marks C 38 visible on bark blaze, and with a healed blaze at the bottom.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C 38 | S 17
T 22 S R 9 W
1970

from which a new bearing tree

A maple, 6 ins. diam., bears N. 38 1/2° W., 25 1/2 lks. dist., mkd. C 38 BT.

Land, mountainous.

Soil, clay loam.

Timber, fir, hemlock, cedar, alder, oak, dogwood, yew and cascara; undergrowth, salal, Oregon grape, hazel, fern, and arrowwood.

S. 89° 47' W., bet. secs. 7 and 18.

Descend 70 ft. over W. slope. through scattering timber and dense undergrowth.

- 2.15 Gravelled road, 20 lks. wide, bears N. 15° W. and S. 15° E.
- 3.90 Dirt road, 10 lks. wide, bears N. 20° W. and S. 10° E.
- 6.50 Dirt road, 15 lks. wide, bears N. 20° W. and S. 20° E.
- 7.90 Left bank of the Umpqua River, course S.; thence across river.
- 16.70 Right bank of the Umpqua River; asc. 520 ft. over broken E. slope.
- 19.65 State Highway No. 38, 30 lks. wide, bears N. and S.

SEE M 93-58 for further INFORMATION 11/10/65 3/86